

Form 3160-5  
June 1990)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

**SUBMIT IN TRIPLICATE**

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Petroleum Development Corporation

3. Address and Telephone No.

9720-B Candelaria NE, Albuquerque, NM 87112 505-293-4044

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980'FSL, 660'FWL, Sec. 8, T8S, R31E

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

5. Lease Designation and Serial No.

NM 15016

6. If Indian, Allottee or Tribe Name

7. If Unit or C.A. Agreement Designation

8. Well Name and No.

Wattam Federal #2

9. API Well No.

3000 520811

10. Field and Pool, or Exploratory Area

Tom-Tom

11. County or Parish, State

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice


TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other Horizontal  
☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form 1)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

- 1) Cement squeeze perf 3646' to 3798'.
- 2) Mill 5½" casing 3472'-3547'.
- 3) Ran directional survey. Location of hole at 3522', compared to surface location: 28' North and 16' East.
- 4) Set cement plug and drilled out to 3522', KOP.
- 5) Drilled arc from 3522' to 3832'. Drilled horizontal hole, 4-3/4", from 3832' to 5689' MD. TVD 3715'-3745'. End of lateral from surface location: 1870 N and 931 E.
- 6) Acidized w/25,000 gals. 15% acid.
- 7) 8/4/94 pumped 70 BO and 140 BW, 100 MCF in 24 hrs.



AUG 19 1994

14. I hereby certify that the foregoing is true and correct

Signed J.C. Johnson  
(This space for Federal or State office use)

Title President

Date 8/16/94

Approved by \_\_\_\_\_  
Conditions of approval, if any:

Title \_\_\_\_\_

ACCEPTED FOR RECORD  
PETER W. CHESTER  
Date \_\_\_\_\_

AUG 26 1994

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*See Instruction on Reverse Side

BUREAU OF LAND MANAGEMENT  
ROSWELL RESOURCE AREA

