

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N. M. OIL CONS. COMMISSION
P. O. BOX 1980
HOBBS, NEW MEXICO 88240

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Petroleum Development Corporation

3. Address and Telephone No.

9720 B Candelaria N.E. Albuquerque, NM 87112 (505) 293-4044

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit Letter F, 1980' FNL, 1980' FWL, Section 6, T8S, R31E

5. Lease Designation and Serial No.

NM 15016

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Wattam Federal #3

9. API Well No.

30-005-20812

10. Field and Pool, or Exploratory Area

Cato San Andres

11. County or Parish, State

Chaves County, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☒ Casing Repair
☐ Altering Casing
☒ Other Clean out plugged lateral & run plastic liner.
- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☒ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 1) Set retrievable bridge plug @ 3620'. Dump 2 sacks frac sand.
- 2) Run packer, pressure up with pump truck, locate casing leak. (If necessary pump small amount of acid in casing leak to break down.)
- 3) Squeeze cement the hole in casing and drill out.
- 4) Clean out plugged arc in lateral with foam air compressor.
- 5) Run a 3 inch plastic liner below tubing through arc in lateral, place well back on production test.

14. I hereby certify that the foregoing is true and correct

Signed

[Signature]

Title Production Manager

Date 3-5-91

(This space for Federal or State/office use)

Approved by

Conditions of approval, if any:

Title

APPROVED
PETER W. CHESTER

MAR 7 1991

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

BUREAU OF LAND MANAGEMENT
ROSWell RESOURCE AREA

RECEIVED

MAR 8 1961

U.S. DEPARTMENT OF AGRICULTURE
WASHINGTON, D.C.