DEPARTMENT OF TH INTERIORQUI CNNS. CONSUMPT SSUMPS - 3016 GEOLOGICAL SURVEY P. 0. BOX 1950 HORDE. NEW MEXICS 6. FF. MDIAN, ALLOTTEE OR TRIBE NAME BREACH STATUS 6. FF. MDIAN, ALLOTTEE OR TRIBE NAME SUNDRY NOTICES AND REPORTS ON WELLS 6. FARM OR LEASE NAME 8. FARM OR LEASE NAME Do not us this form for proposation or plue back to a different well ID other 9. WELL NO. 2. NAME OF OPERATOR EXXOR COPERATOR 9. WELL NO. 2. NAME OF OPERATOR EXXOR COPERATOR 10. FIELD OR WILCAT NAME Down J. AT TOTAL DOF WELL (REPORT LOCATION CLEARLY, See space 17 below.) 3. ADDRESS OF OPERATOR 50. T. T8.S. R - 31E AT SURFACE: 613.' FNL and 782' FEL OF Section AT TOP FROD. INTERVAL: AT TOP FROD. INTERVAL: AT TOP FROD. INTERVAL: AT TOP ROD. INTERVAL: AT TOTAL DEFTH: 11. SEC. T. T8.S. R - 31E 5. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA 14. AFI NO. 15. ELEVATIONS (SHOW DF, KDB. AND WD Later 15. ELEVATIONS (SHOW DF, KDB. AND WD Later 20 CULST FOR APPROVAL TO: SUBSEQUENT REPORT OF: 20 CULT OF ALTER CASING MANDONA' 10. DETING MALLS, and give subsurface locations and change on Form 3-300 3. JOINTS 1260 Feet 8 5/8", 24# K-55 casing set at 1271'. Cement %/600 sx lite, tailed %/250 sx Cl "C". 24. CACL POB at 6:30 p.m., 2-2-82, circulated 135 sx. WOC 18 1/2 hours. D	UNITED STAT	2C	Budget Bursau No. 42-R142	
GebLoGiCAL SURVEY P. O. BOX 1930 SUNDRY NOTICES AND REPORTS ON WELLS SUNDRY NOTICES AND REPORTS ON WELLS On the bit of the off off off off off off off off off of		INTERIORALL CANS. COM		
INDEX IN UNIT AGREEMENT NAME SUNDRY NOTICES AND REPORTS ON WELLS T. UNIT AGREEMENT NAME Dand use the despen or plug back to a different a dia this form for properties to despen or plug back to a different a well colspan="2">Construction a well colspan="2">Construction b diameter statum Frederal a ADDRESS of OPERATOR 9. WELL NO. Box 1600, Midland, TX 79702 10. FIELD OR WILDCAT NAME To Der North Der WELL (REPORT LOCATION CLEARLY. See space 17 Sec 7, T8.S, R31E AT TOP PROD. INTERVENT and 782' FEL of Sectic diaves AT TOP PROD. INTERVENT and 782' FEL of Sectic diaves AT TOP APRON. MICK DATA SUBSEQUENT REPORT OF: SET WATER SUTORF CASING SUBSEQUENT REPORT OF: REPORT, OR OTHER DATA Colspan="2">Conservent of from 9-330 EQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: SET WATER SUTORF Colore MARCE ZONNES Colore BANDONA Colore MARCE TREAT Colore Colores Colores Spudded 12 1/4" hole at 1:30 a.m. 2-1-82. Drilled 12 1/4" hole at	GEOLOGICAL SU	RVEY P. O. BOX 1980	6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
Db not use this form for poperate to this or to descent or plug back to a different distance in the property of the propreceeperty of the property of the property of the prope	SUNDRY NOTICES AND RE		88240	
1. oil well IXI well other B. PARM OR LEASE NAME 2. NAME OF OPERATOR 9. WELL NO. 6. ADDRESS OF OPERATOR 9. WELL NO. 3. ADDRESS OF OPERATOR 10. FIELD OR WILDCAT NAME 3. ADDRESS OF OPERATOR 10. FIELD OR WILDCAT NAME 3. ADDRESS OF OPERATOR 10. FIELD OR WILDCAT NAME 3. ADDRESS OF OPERATOR 10. FIELD OR WILDCAT NAME 3. ADDRESS OF OPERATOR 10. FIELD OR WILDCAT NAME 3. ADDRESS OF OPERATOR 10. FIELD OR WILDCAT NAME 3. ADDRESS OF OPERATOR 10. FIELD OR WILDCAT NAME 3. ADDRESS OF OPERATOR 10. FIELD OR WILDCAT NAME 3. ADDRESS OF OPERATOR 10. FIELD OR WILDCAT NAME 3. CACTION OF WELL (REPORT LOCATION CLEARLY. See space 17 Sec. 7. T. T-8.S. R31E AT TOP PRODOI. INTERVAL AT TOP PROVAL TO: SUBSEQUENT REPORT OF: 14. OR ADREDWERTE ON TO INDICATE NATURE OF NOTICE. IS. ELEVATIONS (SHOW DF. KDB, AND WD EQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: Is. ELEVATIONS (SHOW DF. KDB, AND WD ACTIVE REAT INTERVERT, OR OTHER DATA Is. ELEVATIONS (SHOW DF. KDB, AND WD JUL TOR COMPLTE OPERATORY STATE AND PROVAL TO: SHOW DF. KDB, AND WD JUL THEL COMPLTE OPERATORY STATE AND WO'	Do not use this form for opposite to drill on to .	PURIS UN WELLS		
well 20 well 20 other 9. WELL NO. 2. NAME OF OPERATOR 9. WELL NO. 3. ADDRESS OF OPERATOR 10. FIELD OR WILDCAT NAME 2. ADDRESS OF OPERATOR 11. SEC. T., R. M., OR BLK. AND SURVEY O AREA NAME AND SURVEY O AT TOP PROD. Midland, TX 79702 11. SEC. T., R. M., OR BLK. AND SURVEY O AT TOP PROD. Midland, TX 79702 11. SEC. T., R. M., OR BLK. AND SURVEY O AT TOP PROD. Midland, TX 79702 11. SEC. T., R. M., OR BLK. AND SURVEY O AT TOP PROD. Midland, TX 79702 11. SEC. T., R. M., OR BLK. AND SURVEY O AT TOP PROD. MIDDRATE BOX TO INDICATE NATURE OF NOTICE 12. COUNTY OR PARISH 13. STATE CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE 14. API NO. EQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TOTAL DETTH: 13. ELEVATIONS (SHOW DF, KDB. AND WD LATE CASING MANGE ZONE 14. API NO. TO CONCRETE BADOMESE 14. API NO. BANDOON 14. API NO. TOTO ALDETTH: 14. API NO. TO CONCRETE REPORTORSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates INTER CASING 10. TE CASING WILL OR ALTER CASING 10. STATE Spudded 12 1/4" hole at 1:30 a.m	1. oil gas		8. FARM OR LEASE NAME	
Exxon Corporation 10. FIELD OR WILDCAT NAME 3. ADDRESS OF OPERATOR Tomahawk Box 1500, Midland, TX 79702 11. SEC. T. R. M., OR BLK. AND SURVEY O AL COATION OF WELL (REPORT LOCATION CLEARLY. See space 17 AT TOP PROD. INTERVAL: AT TOP PROD. INTERVAL: AT TOP ROD. INTERVAL: AT TOP ROD. INTERVAL: AT TOP ROD. INTERVAL: AT TOP ROD. INTERVAL: AT TOTAL DEPTH: 11. SEC. T. R. M., OR BLK. AND SURVEY O .Sec. 7, T-85, R-31E 6. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE REPORT, OR OTHER DATA 12. COUNTY OF PARISH 13. STATE Chaves 13. STATE Chaves EQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: SUBSEQUENT REPORT OF: 14. API NO. EQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: INOTE: Report results of multiple completion or zon that of most state all pertinent details, and give pertinent details including estimated date of starting any proposed work. If wall is directionally diffied, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to the work.)" 7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates including estimated date of starting any proposed work. If wall is directionally diffied, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to the work.)" Spudded 12 1/4" hole at 1:30 a.m. 2-1-82. Drilled 12 1/4" hole to 1278'. Ran 30 joints 1260 feet 8 5/8", 24# K-55 casing set at 1271'. Cement %/600 sx lite, tailed w/250 sx Cl "C". 2% CaCl POB at 6:30 p.m. 2-2-82, circulated 135 sx. WOC 18 1/2 hours. Tested casing w/1000# held OK. Drilled plug and	well well other			
ADDRESS OF OPERATOR ADDRESS ADDRESS OF OPERATOR ADDRESS A				
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AREA to the industry of blc. AND SURVEY of Sec. 7, T-85, R-31E AT TOP PROD. INTERVAL: AT TOTAL DEPTH: and 782' FEL of Section (Chaves) Sec. 7, T-85, R-31E 6. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA Its ELEVATIONS (SHOW DF, KDB, AND WD Later EQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: SUBSEQUENT REPORT OF: New Mexicol Later FARCTURE TREAT HOOT OR ACIDIZE EPAIR WELL ULL OR ALTER CASING ULL OR ALTER C	3. ADDRESS OF OPERATOR			
below) AT SUFFACE: 643' FNL and 782' FEL of Sections Sec. 7, T-85, R-31E AT SUFFACE: 643' FNL and 782' FEL of Sections Clarves Sec. 7, T-85, R-31E AT TOP PROD. INTERVAL: AT TOP PROD. INTERVAL: New Mexic. AT TOTAL DEPTH: BACOMY OF PARISH 13, STATE 6. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. 14, APH NO. 15, ELEVATIONS (SHOW DF, KDB, AND WD Later (NOTE: Report results of multiple completion or zon- change on Form 9-330.) (NOTE: Report results of multiple completion or zon- change on Form 9-330.) (NOTE: Report results of multiple completion or zon- change on Form 9-330.) (NOTE: Report results of multiple completion or zon- change on Form 9-330.) Specified 12 1/4" hole at 1:30 a.m. 2-1-82. Drilled 12 1/4" hole to 1278'. Read as in gw/ proposed work. If wall is directionally drilled, give subsurface locations and convex. <td colspan<="" td=""><td>Box 1600, Midland, TX 79</td><td></td><td>11. SEC., T., R., M., OR BLK. AND SURVEY OF</td></td>	<td>Box 1600, Midland, TX 79</td> <td></td> <td>11. SEC., T., R., M., OR BLK. AND SURVEY OF</td>	Box 1600, Midland, TX 79		11. SEC., T., R., M., OR BLK. AND SURVEY OF
AT TOTAL DEPTH: 6. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: 14. API NO. 15. ELEVATIONS (SHOW DF, KDB, AND WO Later 15. ELEVATIONS (SHOW DF, KDB, AND WO Later II. ELEVATIONS (CHOW DF, KDB, AND WO Later II. ELEVATIONS (SHOW DF, KDB, AND WO Later II. ELEVATIONS (CHOW DF, KDB, AND WO Later III. ELEVATIONS (CHOW DF, KDB, AND WO IIII. ELEVATIONS (CHOW DF, KDB, AND WO IIIII. ELEVATIONS (CHOW DF, KDB, AND WO IIIII. ELEVATIONS (CHOW DF, KDB, AND WO IIIII. ELEVATIONS (CHOW DF, KDB, AND WO IIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII	below.)		AREA Sec. 7. T-8S. R-31E	
		82' FEL of Sectio	n 12. COUNTY OR PARISH 13. STATE Chaves New Mexico	
REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: II. ELEVATIONS (SHOW DF, KOB, AND WO Later REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: III. CALLER SHUT-OFF III. CALLER SHUT-OFF III. OR ALTER SHUT-OFF III. OR ALTER SHUT-OFF III. OR ALTER CASING WILLTPLE COMPLETE PALKOE ZOMES BRANDON* III. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Spudded 12 1/4" hole at 1:30 a.m. 2-1-82. Drilled 12 1/4" hole to 1278'. Ran 30 joints 1260 feet 8 5/8", 24# K-55 casing set at 1271'. Cement VB/600 sx lite, tailed W/250 sx Cl "C". 2% CaCl POB at 6:30 p.m. 2-2-82, circulated 135 sx. WOC 18 1/2 hours. Drilled plug and cement 1:00 p.m. 2-3-82. Drilling. Wuburdes Safety Valve: Manu. and Type Set Q III. CARLER III. CARLER Set G III. CARLER III. CARLER II	16. CHECK APPROPRIATE BOX TO INDIC	ATE NATURE OF NOTICE	14. API NO.	
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: Later TEST WATER SHUT-OFF Image: Construction of the second se	REPORT, OR OTHER DATA		15. ELEVATIONS (SHOW DF. KDB. AND WO	
FRACTURE TREAT SHOOT OR ACIDIZE SHOOT OR ACIDIZE SHOOT OR ACIDIZE (NOTE: Report results of multiple completion or zero change on Form 9-330.) (NOTE: Report results of multiple completion or zero change on Form 9-330.) (NOTE: Report results of multiple completion or zero change on Form 9-330.) (NOTE: Report results of multiple completion or zero change on Form 9-330.) (NOTE: Report results of multiple completion or zero change on Form 9-330.) (NOTE: Report results of multiple completion or zero change on Form 9-330.) (NOTE: Report results of multiple completion or zero change on Form 9-330.) (NOTE: Report results of multiple completion or zero change on Form 9-330.) (NOTE: Report results of multiple completion or zero change on Form 9-330.) (NOTE: Report results of multiple completion or zero change on Form 9-330.) (NOTE: Report results of multiple completion or zero change on Form 9-330.) (NOTE: Report results of multiple completion or zero change on Form 9-330.) (NOTE: Report results of multiple completion or zero change on Form 9-330.) (NOTE: Report results of multiple completion or zero change on Form 9-330.) (NOTE: Report results of multiple completion or zero change on Form 9-330.) (NOTE: Report results of multiple completion or zero change on Form 9-330.) (NOTE: Report results of results (NOTE: Report results of results (NOTE: Report results of multiple completion or zero change on Form 9-330.) (NOTE: Report results of results (NOTE: Report results of results (NOTE: Report results of results (NOTE: Report re	REQUEST FOR APPROVAL TO: SUE	SEQUENT REPORT OF:	Later	
SHOOT OR ACIDIZE (NOTE: Report results of multiple completion or zone change on Form 9-330.) VULL OR ALTER CASING (NOTE: Report results of multiple completion or zone change on Form 9-330.) VULL OR ALTER CASING (NOTE: Report results of multiple completion or zone change on Form 9-330.) VULTOP ALTER CASING (NOTE: Report results of multiple completion or zone change on Form 9-330.) VILL OR ALTER CASING (NOTE: Report results of multiple completion or zone change on Form 9-330.) VILL OR ALTER CASING (NOTE: Report results of multiple completion or zone change on Form 9-330.) VILL OR ALTER CASING (Intervention of the change on Form 9-330.) VILL OR ALTER CASING (Intervention of the change on Form 9-330.) VILL OR ALTER CASING (Intervention of the change on Form 9-330.) VILL OR ALTER CASING (Intervention of the change on Form 9-330.) VILL OR ALTER CASING (Intervention of the change on Form 9-330.) Spudded 12 1/4" hole at 1:30 a.m. 2-1-82. Drilled 12 1/4" hole at 1:278". Ran 30 joints 1260 feet 8 5/8", 24# K-55 casing set at 1271". Cement V8/600 sx lite, tailed w/250 sx Cl "C". 2% Call POB at 6:30 p.m. 2-2-82, circulated 135 sx. WOC 18 1/2 hours. Tested casing w/1000# held 0K. Drilled plug and cement 1:00 p.m. 2-3-82.				
DULL OR ALTER CASING Image on Form 3-330.) MULTIPLE COMPLETE Image on Form 3-330.) InANGE ZONES Image on Form 3-330.) ISDESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Spudded 12 1/4" hole at 1:30 a.m. 2-1-82. Drilled 12 1/4" hole to 1278'. Ran 30 joints 1260 feet 8 5/8", 24# K-55 casing set at 1271'. Cement ve/600 sx lite, tailed w/250 sx Cl "C". 2% CaCl POB at 6:30 p.m. 2-2-82, circulated 135 sx. WOC 18 1/2 hours. Tested casing w/1000# held OK. Drilled plug and cement 1:00 p.m. 2-3-82. Drilling. ubsurface Safety Valve: Manu. and Type Set @ At hereby certify that the foregoing is true and correct Index of the composed for Federal or State office use) Perover law Perover law ONDITIONS OF APMARM '9 4982	SHOOT OR ACIDIZE			
AULTIPLE COMPLETE Image on Form 9-330.) HANGE ZONES Image on Form 9-330.) HANGE ZONES Image on Form 9-330.) StanDon* Image on Form 9-330.) other Image on Form 9-330.) 7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Spudded 12 1/4" hole at 1:30 a.m. 2-1-82. Drilled 12 1/4" hole to 1278'. Ran 30 joints 1260 feet 8 5/8", 24# K-55 casing set at 1271'. Cement VM/600 sx lite, tailed w/250 sx Cl "C". 2% CaCl POB at 6:30 p.m. 2-2-82, circulated 135 sx. WOC 18 1/2 hours. Tested casing w/1000# held OK. Drilled plug and cement 1:00 p.m. 2-3-82. Drilling. ubsurface Safety Valve: Manu. and Type Start Control Start Control Multiple Plug and cement 1:00 p.m. 2-3-82. Drilling. ubsurface Safety Valve: Manu. and Type Start Control Additional control Additional control RCGL R A. CHAPMAN This space for Federal or State office use)			(NOTE: Report results of multiple completion or zone	
BBANDON* Image: Control of the spectrum of the s			change on Form 9-330.)	
7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Spudded 12 1/4" hole at 1:30 a.m. 2-1-82. Drilled 12 1/4" hole to 1278'. Ran 30 joints 1260 feet 8 5/8", 24# K-55 casing set at 1271'. Cement V8/600 sx lite, tailed w/250 sx Cl "C". 2% CaCl POB at 6:30 p.m. 2-2-82, circulated 135 sx. WOC 18 1/2 hours. Tested casing w/1000# held OK. Drilled plug and cement 1:00 p.m. 2-3-82. Drilling. ubsurface Safety Valve: Manu. and Type Start for FOR RECORD All hereby certify that the foregoing is true and correct GRED THLEST. AdministraotroArte All hereby certify that the foregoing is true and correct OPERATIONS OF APMARY 19 4982				
measured and true vertical depths for all markers and zones pertinent to this work.)* Spudded 12 1/4" hole at 1:30 a.m. 2-1-82. Drilled 12 1/4" hole at 1:78". Ran 30 joints 1260 feet 8 5/8", 24# K-55 casing set at 1271'. Cement %/600 sx lite, tailed w/250 sx Cl "C". 2% CaCl POB at 6:30 p.m. 2-2-82, circulated 135 sx. WOC 18 1/2 hours. Tested casing w/1000# held OK. Drilled plug and cement 1:00 p.m. 2-3-82. Drilling. ubsurface Safety Valve: Manu. and Type S. I hereby certify that the foregoing is true and correct GNED THLEST. Administraotroate ACCIERA A. CHAPMAN This space for Federal or State office use) PEROVED BY				
Cement %/600 sx lite, tailed w/250 sx Cl "C". 2% CaCl POB at 6:30 p.m. 2-2-82, circulated 135 sx. WOC 18 1/2 hours. Tested casing w/1000# held OK. Drilled plug and cement 1:00 p.m. 2-3-82. Drilling. Set @	ABANDON*	O OPERATIONS (Clearly state	all pertinent details, and give pertinent dates.	
Cement %/600 sx lite, tailed w/250 sx Cl "C". 2% CaCl POB at 6:30 p.m. 2-2-82, circulated 135 sx. WOC 18 1/2 hours. Tested casing w/1000# held OK. Drilled plug and cement 1:00 p.m. 2-3-82. Drilling. Set @	ABANDON* (other) 17. DESCRIBE PROPOSED OR COMPLETE including estimated date of starting an measured and true vertical depths for a Spudded 12 1/4" hole at	1 markers and zones pertinem	a all pertinent details, and give pertinent dates, rectionally drilled, give subsurface locations and t to this work.)*	
2% CaCl POB at 6:30 p.m. 2-2-82, circulated 135 sx. WOC 18 1/2 hours. Tested casing w/1000# held OK. Drilled plug and cement 1:00 p.m. 2-3-82. Drilling. Set @	ABANDON* (other)	1:30 a.m. 2-1-82.	t to this work.)*	
Tested casing w/1000# held OK. Drilled plug and cement 1:00 p.m. 2-3-82. Drilling. Set @	ABANDON* (other)	1:30 a.m. 2-1-82. 1278'. 3 5/8", 24# K-55 (casing set at 1271'.	
Drilled plug and cement 1:00 p.m. 2-3-82. Drilling. ubsurface Safety Valve: Manu. and Type	ABANDON* other)	1:30 a.m. 2-1-82. 1278'. 3 5/8", 24# K-55 d 1ed w/250 sx C1	casing set at 1271'.	
Drilling. ubsurface Safety Valve: Manu. and TypeSet @ B. I hereby certify that the foregoing is true and correct GNED	ABANDON* other) T. DESCRIBE PROPOSED OR COMPLETER including estimated date of starting an measured and true vertical depths for a Spudded 12 1/4" hole at Drilled 12 1/4" hole to Ran 30 joints 1260 feet Cement 12/600 sx lite, ta 2% CaCl POB at 6:30 p.m.	<pre>Imarkers and zones pertinem 1:30 a.m. 2-1-82. 1278'. 3 5/8", 24# K-55 d 1ed w/250 sx C1 v 2-2-82, circulate</pre>	casing set at 1271'.	
B. I hereby certify that the foregoing is true and correct GNED	ABANDON* other) I.7. DESCRIBE PROPOSED OR COMPLETE including estimated date of starting an measured and true vertical depths for a Spudded 12 1/4" hole at Drilled 12 1/4" hole to Ran 30 joints 1260 feet Cement %/600 sx lite, ta 2% CaCl POB at 6:30 p.m. Tested casing w/1000# hei	<pre>Imarkers and zones pertinen 1:30 a.m. 2-1-82. 1278'. 3 5/8", 24# K-55 d 1ed w/250 sx Cl 2-2-82, circulate d OK.</pre>	casing set at 1271'.	
B. I hereby certify that the foregoing is true and correct GNED	ABANDON* other)	<pre>Imarkers and zones pertinen 1:30 a.m. 2-1-82. 1278'. 3 5/8", 24# K-55 d 1ed w/250 sx Cl 2-2-82, circulate d OK.</pre>	casing set at 1271'.	
IGNED	ABANDON* (other)	<pre>1:30 a.m. 2-1-82. 1278'. 3 5/8", 24# K-55 d 1ed w/250 sx Cl v 2-2-82, circulate d OK. :00 p.m. 2-3-82.</pre>	casing set at 1271'. "C". ed 135 sx. WOC 18 1/2 hours.	
ROGER A. CHAPMAN (This space for Federal or State office use) ROGEVELL, TRANSPORTED BY TITLE DATE DATE	ABANDON* (other) 17. DESCRIBE PROPOSED OR COMPLETER including estimated date of starting an measured and true vertical depths for a Spudded 12 1/4" hole at Drilled 12 1/4" hole at Ran 30 joints 1260 feet Cement %/600 sx lite, ta 2% CaCl POB at 6:30 p.m. Tested casing w/1000# he Drilled plug and cement Drilled plug and cement Drilling.	<pre>Imarkers and zones pertinent 1:30 a.m. 2-1-82. 1278'. 3 5/8", 24# K-55 d 1ed w/250 sx C1 d 2-2-82, circulate d OK. :00 p.m. 2-3-82.</pre>	casing set at 1271'. "C". ed 135 sx. WOC 18 1/2 hours.	
DNDITIONS OF APMARY 19 1982	ABANDON* other) 17. DESCRIBE PROPOSED OR COMPLETER including estimated date of starting an measured and true vertical depths for a Spudded 12 1/4" hole at Drilled 12 1/4" hole at Ran 30 joints 1260 feet Cement %/600 sx lite, ta 2% CaCl POB at 6:30 p.m. Tested casing w/1000# he Drilled plug and cement Drilled plug and cement Drilling. ubsurface Safety Valve: Manu. and Type 8. I hereby certify that the foregoing is true	<pre>I markers and zones pertinent 1:30 a.m. 2-1-82. 1278'. 3 5/8", 24# K-55 d 1ed w/250 sx C1 f 2-2-82, circulate d OK. :00 p.m. 2-3-82. and correct</pre>	casing set at 1271'. "C". ed 135 sx. WOC 18 1/2 hours.	
ONDITIONS OF APRIARY 19 4982	ABANDON* (other) 17. DESCRIBE PROPOSED OR COMPLETE including estimated date of starting an measured and true vertical depths for a Spudded 12 1/4" hole at Drilled 12 1/4" hole at Drilled 12 1/4" hole to Ran 30 joints 1260 feet Cement %/600 sx lite, ta 2% CaCl POB at 6:30 p.m. Tested casing w/1000# he: Drilled plug and cement Drilled plug and cement Drilling. Subsurface Safety Valve: Manu. and Type 8. I hereby certify that the foregoing is true IGNED	Imarkers and zones pertinent 1:30 a.m. 2-1-82. 1278'. 3 5/8", 24# K-55 of 3 5/8", 24# K-55 of 1ed w/250 sx Cl 1 2-2-82, circulate .d 0K. :00 p.m. 2-3-82.	casing set at 1271'. "C". ed 135 sx. WOC 18 1/2 hours. Set @ $\frac{112}{12}$ 11	
	ABANDON* (other) 17. DESCRIBE PROPOSED OR COMPLETER including estimated date of starting an measured and true vertical depths for a Spudded 12 1/4" hole at Drilled 12 1/4" hole at Drilled 12 1/4" hole to Ran 30 joints 1260 feet Cement %/600 sx lite, ta 2% CaCl POB at 6:30 p.m. Tested casing w/1000# he: Drilled plug and cement Drilled plug and cement Drilling. Subsurface Safety Valve: Manu. and Type 8. I hereby certify that the foregoing is true IGNED REGIER A. CHAPMAN	Imarkers and zones pertinent 1:30 a.m. 2-1-82. 1278'. 3 5/8", 24# K-55 of 3 5/8", 24# K-55 of 1ed w/250 sx Cl 1 2-2-82, circulate .d 0K. :00 p.m. 2-3-82.	casing set at 1271'. "C". ed 135 sx. WOC 18 1/2 hours. Set @ $\frac{112}{12}$ 11	
U.S. GEOLOGICAL SURVEY	ABANDON* (other) 17. DESCRIBE PROPOSED OR COMPLETER including estimated date of starting an measured and true vertical depths for a Spudded 12 1/4" hole at Drilled 12 1/4" hole to Ran 30 joints 1260 feet Cement %/600 sx lite, ta 2% CaCl POB at 6:30 p.m. Tested casing w/1000# he: Drilled plug and cement Drilled plug and cement Drilling. Subsurface Safety Valve: Manu. and Type 8. I hereby certify that the foregoing is true IGNED	1:30 a.m. 2-1-82. 1:78'. 3 5/8", 24# K-55 d 1ed w/250 sx Cl 2-2-82, circulate .d OK. :00 p.m. 2-3-82.	casing set at 1271'. "C". ed 135 sx. WOC 18 1/2 hours. Set @Set @ AR 1 aotroate3/10/82 use)	
	ABANDON* other) I.7. DESCRIBE PROPOSED OR COMPLETER including estimated date of starting an measured and true vertical depths for a Spudded 12 1/4" hole at Drilled 12 1/4" hole to Ran 30 joints 1260 feet Cement %/600 sx lite, ta 2% CaCl POB at 6:30 p.m. Tested casing w/1000# he: Drilled plug and cement Drilled plug and cement Drilling. Ubsurface Safety Valve: Manu. and Type B. I hereby certify that the foregoing is true GNED	1:30 a.m. 2-1-82. 1:78'. 3 5/8", 24# K-55 d 1ed w/250 sx Cl 2-2-82, circulate .d OK. :00 p.m. 2-3-82.	casing set at 1271'. "C". ed 135 sx. WOC 18 1/2 hours. Set @Set @ AR 1 aotroate3/10/82 use)	

•

:

.....

ţ

.

U.C.A. HOBAS CHRICE

APR 2 1982

RECSIVED

1