

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION  
P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease  
State ☐ Fee ☒  
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

7. Unit Agreement Name

Name of Operator

Yates Petroleum Corporation

8. Farm or Lease Name  
Paul LR

Address of Operator

207 South 4th St., Artesia, NM 88210

9. Well No.  
5

Location of Well

UNIT LETTER B 660 FEET FROM THE North LINE AND 1980 FEET FROM  
THE East LINE, SECTION 25 TOWNSHIP 7S RANGE 31E NMPM.

10. Field and Pool, or Wildcat  
Tom Tom SA

15. Elevation (Show whether DF, RT, GR, etc.)  
4388' GR

12. County  
Chaves

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐  
OTHER ☐

PLUG AND ABANDON ☐  
CHANGE PLANS ☐  
OTHER ☐

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☐  
CASING TEST AND CEMENT JOB ☐  
OTHER Perforate & Treat ☐

ALTERING CASING ☐  
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1503.

TD 4456'. WIH w/Steel Strip gun on wireline & perforated 4356-4445' w/16 .50" holes as follows: 4356, 57-1/2, 72, 73, 76, 77, 91-1/2, 96, 97-1/2, 4402, 09-1/2, 19, 25, 27, 35, & 45'. Acidized perforations 4356-4445' w/2500 gallons 20% DS-30 & 35 ball sealers. Flow back & swabbed well. No show of oil or gas. Set CIBP at 4345' w/20' cement on top. WIH w/Steel Strip gun on wireline & perforated 4049-4096' w/9 .50" holes as follows: 4049, 51, 63, 69, 79, 86, 88, 90 & 96'. Acidized perforations 4049-4096' w/1500 gallons 20% NEFE acid & 9 ball sealers. Swabbed well to recover load. Set pumping equipment.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature]

TITLE Engineering Secretary

DATE 9-2-81

Only Signed By

Jerry Seaton

APPROVED BY [Signature]

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: