

OIL CONSERVATION DIVISION

P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease  
State ☐ For ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

Name of Operator

Yates Petroleum Corporation

Address of Operator

207 South 4th St., Artesia, NM 88210

Location of Well

UNIT LETTER B 660 FEET FROM THE North LINE AND 1980 FEET FROM  
THE East LINE, SECTION 25 TOWNSHIP 7S RANGE 31E NMPM.

7. Unit Agreement Name

8. Farm or Lease Name

Paul LR

9. Well No.

5

10. Field and Pool, or Wildcat

Tom Tom SA

15. Elevation (Show whether DF, RT, GR, etc.)

4388' GR

12. County

Chaves

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

REMEDIAL WORK ☐

ALTERING CASING ☐

TEMPORARILY ABANDON ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

REPAIR OR ALTER CASING ☐

CHANGE PLANS ☐

CASING TEST AND CEMENT JOBS ☒

OTHER ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 12-1/4" hole 9:00 AM 7-26-81. TD 1621'. Ran 40 joints of 8-5/8" 24# K-55 8rd casing set at 1621'. 1-Texas Pattern guide shoe at 1621'. 1-Flapper insert float set at 1582'. Cemented w/500 sacks 50/50 Poz. Tailed in w/150 sacks Class "C" 3% CaCl. PD 9:00 PM 7-29-81. Bumped plug to 1500 psi, released pressure and float held okay. Compressive strength 1000 psi. Circulated 35 sacks. WOC 18 hrs. TD 4456'. Ran 110 joints of 4-1/2" 9.5# K-55 of casing set at 4456'. 1-Regular guide shoe at 4456'. Float collar at 4417'. Cemented w/350 sacks Class "C" 3% salt. PD 2:45 AM 8-9-81. Bumped plug to 1350 psi, released pressure and float held okay.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

*Jerry Sexton*

TITLE Engineering Secretary

DATE 8-19-81

Only Signed In  
Jerry Sexton

APPROVED BY *Don H. Pugh*

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: