

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease  
State ☐ Fee ☒  
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

7. Unit Agreement Name

1. Name of Operator

Yates Petroleum Corporation

8. Farm or Lease Name

Paul "LR"

2. Address of Operator

207 South 4th St., Artesia, NM 88210

9. Well No.

6

3. Location of Well

UNIT LETTER C 660 FEET FROM THE North LINE AND 1980 FEET FROM  
THE West LINE, SECTION 25 TOWNSHIP 7S RANGE 31E NMPM.

10. Field and Pool, or Whicat

Tom Tom SA

15. Elevation (Show whether DF, RT, GR, etc.)

4380' GR

12. County

Chaves

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐

PLUG AND ABANDON ☐  
CHANGE PLANS ☐

REMEDIAL WORK ☐  
COMMENCE DRILLING OPWS. ☐  
CASING TEST AND CEMENT JOBS ☐

ALTERING CASING ☐  
PLUG AND ABANDONMENT ☐

OTHER ☐

OTHER Production casing, perforate, treat

16. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 4250'. Ran 104 joints of 4-1/2" 9.5# casing set at 4250'. 1-regular guide shoe at 4250'. Float collar at 4210'. Cemented w/300 sacks Class "C" & 3% salt. PD 7:45 AM 8-23-81. Bumped plug to 1000 psi, released pressure and float held okay. WOC. WIH w/Steel Strip gun on wireline & perforated 4110-4125' w/10 .50" holes as follows: 4110, 11, 12, 13, 17, 18, 19, 23, 24 and 25'. Set packer at 4057'. Acidized perfs w/1000 gallons 20% NEFE acid & 25 ball sealers. WIH w/Steel Strip gun on wireline & perforated 4011-4058-1/2'. w/15 .50" holes as follows: 4011, 15, 19, 24, 28, 31, 36, 39, 41, 43, 45, 47, 51, 56 & 58-1/2'. TIH w/4-1/2" RTTS & RBP. Set RBP at 4086'. Test RBP to 2500 psi, OK. Set RTTS at 3974'. Acidized w/2500 gallons 20% NEFE acid & 30 ball sealers. Flowed back & swabbed. TOOH w/packer & RBP. Set pumping equipment.

17. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Jerry Sexton Engineering Secretary

TITLE Engineering Secretary

DATE 9-4-81

Check Signed By

Jerry Sexton

APPROVED BY Jerry Sexton

TITLE

DATE

SEP 8 1981

CONDITIONS OF APPROVAL, IF ANY: