

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION

P.O. BOX 100
SANTA FE, NEW MEXICO 87401

Form C-103
Revised 11-1-

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO EXTEND EXISTING WELLS. IT IS THE EXCLUSIVE PROPERTY OF THE STATE OF NEW MEXICO.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

Name of Operator

Yates Petroleum Corporation

Address of Operator

207 South 4th St., Artesia, NM 88210

Location of Well

UNIT LETTER K 1980 FEET FROM THE South 1980 FEET FROM THE West LINE, SECTION 36 TOWNSHIP 7S RANGE 11E COUNTY Chaves

15. Elevation (Surface or Bottom of Well) 4389'

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

TEMPORARILY ABANDON ☐

REEL OR ALTER CASING ☐

OTHER ☐

PLUG AND ABANDON ☐

CHANGE PLANS ☐

REMEDIAL WORK ☐

COMMENCE DRILLING OPERATIONS ☐

CASING TEST AND CEMENT JOBS ☐

ALTERING CASING ☐

PLUG AND ABANDONMENT ☐

Production Csg., Perforate & Treat ☒

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 4200'. Ran 102 joints of 4-1/2" 9.5# K-55 STAG casing set at 4200'. Flapper shoe at 4200'. Cemented w/250 sacks Class C w/E salt. TD 4:30 AM 10-9-81. Bumped plug to 1200 psi, released pressure & float held OK. WIH & perforated 4089-4113-1/2' w/10 .40" holes as follows: 4089, 91, 93, 95, 104, 95, 96, 99, 10, & 13-1/2'. Set RBP at 4130'. Acidized perforations 4089-4113-1/2' w/2000 gallons 20% NEFE acid & 25 ball sealers. Moved RBP to 4075'. WIH & perforated 4035-4071' w/16 .40" holes as follows: 4035, 36, 37, 38, 41-1/2, 46, 47-1/2, 55, 57-1/2, 59-1/2, 61, 62, 64, 66, 68-1/2 & 71'. Acidized perforations 4035-4071' w/3000 gallons 20% NEFE acid & ball sealers. Moved RBP to 4028'. WIH & perforated 3973-4014' w/10 .40" holes as follows: 3973, 86, 88, 93, 95, 97, 99, 4012, 13 & 14'. Acidized perforations 3973-4014' w/2000 gallons 20% NEFE acid & 20 ball sealers.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signature [Signature] TITLE Engineering Secretary

DATE 10-22-81

COPIES BY [Signature]

TITLE [Signature]

DATE 1981

CONDITIONS OF APPROVAL, IF ANY: