

$$\begin{aligned} \text{Slope} &= -\frac{1}{2} \\ y - 1 &= -\frac{1}{2}(x - 1) \end{aligned}$$

NO. OF COPIES RECEIVED	
DISTRIBUTION	
NAME & PR.	
FILE	
U.I.G.S.	
LAND OFFICE	
OPERATOR	

X

IG 2464

Dovelon, IQ State

3

Tenahawk San Andres

Chaves

COPY NOTICES AND E-MAILS ON VOLUME 10

DO NOT USE THIS FORM FOR RECORDS OF THE FBI. IT IS FOR THE USE OF THE FBI ONLY. IT IS NOT TO BE USED FOR ANY OTHER PURPOSE. IT IS NOT TO BE USED FOR ANY OTHER PURPOSE. IT IS NOT TO BE USED FOR ANY OTHER PURPOSE.

1. OIL ☒ GAS ☐
WELL WELL OTHER-
Name of Operator

Yates Petroleum Corporation
Address of Operator

207 South 4th St., Artesia, NM 88210

c. Location of Wall

UNIT EIGHT N 330 South 200

West 36 7S 3E

$$12. \quad \text{Find } \frac{d}{dx} \left(\frac{1}{x^2} \right) \quad \text{Answer: } -\frac{2}{x^3} \quad \text{Find } \frac{d}{dx} \left(\frac{1}{x^3} \right) \quad \text{Answer: } -\frac{3}{x^4}$$

4414.7' CR

Chaves

Check Appropriate Box To Indicate Nature of Information or Data
NOTICE OF INTENTION TO: ☐ INFORMATION ☐ DATA

10. CONCLUDING REMARKS

PERFORM REMEDIAL WORK ☐

TEMPORARILY ABANDON ☐

HOLD OR ALTER CABING ☐

PLUG AND MOLDING ☐

CHANGE PLUG ☐

RECEIVED
COMMUNICATIONS SECTION
CIVIL SERVICE COMMISSION

ALL INFORMATION CONTAINED
HEREIN IS UNCLASSIFIED

OTNEN

17. Describe Proposed or Contingent Operations (Clearly state all pertinent details, and give exact dates, including date of starting any proposed work) SEE RULE 1103.

TD 4200'. Ran 102 joints of 4-1/2" 9.5# K-55 casing set at 4193'. Auto fill float shoe at 4193'. Cemented w/180 sacks Talc 1:2, 2% CF-2, 2% CaCl₂ & .3% AF-HD. PD 12:00 A.M. (midnight) 12-7-81. Bumped plug to 1500 psi, released pressure & float held, okay. WOC. WIH & perforated 4116-4168-1/2' w/15 .40" holes as follows: 4116, 18, 20, 23, 26, 28½, 33, 49, 53, 59, 60½, 62, 65, 66½ & 68½'. Acidized perforations 4116-4168-1/2' w/2500 gallons 20% NEFE acid & 30 ball sealers. WIH & perforated 2nd zone 4045-4081-1/2' w/15 holes as follows: 4045, 49, 52, 54, 56, 59, 61, 63, 66, 69, 4071½, 4174, 77, 79, & 81½'. Acidized perforations 4045-4081-1/2' w/2500 gallons 20% NEFE acid & 15 ball sealers. WIH & perforated 3rd zone 3954-4010' w/15 holes as follows: 3954, 57, 60, 62, 71, 74, 82, 86, 95½, 98, 4001, 03, 06, 08, & 10'. Acidized perforations 3954-4010' w/2000 gallons 20% NEFE acid & 25 ball sealers.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED: James E. [illegible] TITLE: Engineering Secretary DATE: 12-29-81

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: