Form 0_221		
Form 9-331 Dec. 1973	NN OIL (DD COMMISSIUM BDD Budget Bureau No. 42-R142
	UNITED STATES DIRWET	DD Budget Bureau No. 42-R142 B, W 5. LEASE
DE	PARTMENT OF THE INTERIO	NM-046153-A
	GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
	OTICES AND REPORTS ON WE	
reservoir. Use Form 9-:	for proposals to drill or to deepen or plug back to a 331–C for such proposals.)	8. FARM OR LEASE NAME
1. oil ga		Western Reserves "34"
2. NAME OF OPE	en other	9. WELL NO.
	Reserves Oil Company	# 6 10. FIELD OR WILDCAT NAME
3. ADDRESS OF	OPERATOR	Tom-Tom (San Andres)
	2188 Hobbs, N.M. 88240	11. SEC., T., R., M., OR BLK. AND SURVEY O
4. LOCATION OF below.)	WELL (REPORT LOCATION CLEARLY. See si	pace 17 AREA
AT SURFACE:	1980' FSL & 1980' FWI	$\frac{\text{Sec. 34, T-7-S, R-31-E}}{12. \text{ COUNTY OR PARISH} 13. \text{ STATE}}$
AT TOP PROD.		Chaves N.M.
AT TOTAL DEP		14. API NO.
16. CHECK APPRO REPORT, OR C	PRIATE BOX TO INDICATE NATURE OF N	
		15. ELEVATIONS (SHOW DF, KDB, AND WE
REQUEST FOR APP	ROVAL TO: SUBSEQUENT REPORT	OF: 4305.1' GR
TEST WATER SHUT	FOFF	
SHOOT OR ACIDIZI		
REPAIR WELL		(NOTE: Report results of multiple completion or zor
PULL OR ALTER C MULTIPLE COMPLE	TE \Box $D \subseteq C$	0.4 1981 Change on Form 9–330.)
CHANGE ZONES		
ABANDON*		
(other) Casing	$Test \& other. \square 0.5. GEOLO$	A GAS GICAL SURVEY
· · · · · · · · · · · · · · · · · · ·	rest & other. Roswell, N	VEW MEXICO
17. DESCRIBE PRO	POSED OR COMPLETED OPERATIONS (Clear	WEXICO APPEN MEXICO arly state all pertinent details, and give pertinent date
17. DESCRIBE PRO	PPOSED OR COMPLETED OPERATIONS (Cleared date of starting any proposed work of the starting any proposed work	WEAL SURVEY WEW MEXICO arly state all pertinent details, and give pertinent date well is directionally drilled, give subsurface locations an pertinent to this work.)*
17. DESCRIBE PRC including estim measured and t	POSED OR COMPLETED OPERATIONS (Cleated date of starting any proposed work. If thrue vertical depths for all markers and zones Spud 12 1/4" hole @ 3:3 Ran 36' Jts. (1500') 8	 GICAL SURVEY VEW MEXICO arly state all pertinent details, and give pertinent date: well is directionally drilled, give subsurface locations an pertinent to this work.)* 0 p.m. 11/08/81 5/8" 24# J-55 Casing.
17. DESCRIBE PRC including estim measured and t 11/08.81	POSED OR COMPLETED OPERATIONS (Cleated date of starting any proposed work. If true vertical depths for all markers and zones Spud 12 1/4" hole @ 3:3 Ran 36' Jts. (1500') 8 Set @ 1495'. Cemented	 GICAL SURVEY VEW MEXICO arly state all pertinent details, and give pertinent date: well is directionally drilled, give subsurface locations an pertinent to this work.)* 0 p.m. 11/08/81 5/8" 24# J-55 Casing. w/500 sx. Hal-lite w/ 1/4#/sx.
17. DESCRIBE PRC including estim measured and t 11/08.81	POSED OR COMPLETED OPERATIONS (Cleated date of starting any proposed work. If thrue vertical depths for all markers and zones Spud 12 1/4" hole @ 3:3 Ran 36' Jts. (1500') 8 Set @ 1495'. Cemented Flocele, 5# Gilsonite/s	<pre>GICAL SURVEY VEW MEXICO arly state all pertinent details, and give pertinent date well is directionally drilled, give subsurface locations an pertinent to this work.)* 0 p.m. 11/08/81 5/8" 24# J-55 Casing. w/500 sx. Hal-lite w/ 1/4#/sx. x 2% CaCl followed by 200 sx.</pre>
17. DESCRIBE PRC including estim measured and t 11/08.81	POSED OR COMPLETED OPERATIONS (Cleated date of starting any proposed work. If firme vertical depths for all markers and zones Spud 12 1/4" hole @ 3:3 Ran 36' Jts. (1500') 8 Set @ 1495'. Cemented Flocele, 5# Gilsonite/s Class "C" 2% CaCl. Ful	<pre>GICAL SURVEY VEW MEXICO arly state all pertinent details, and give pertinent date well is directionally drilled, give subsurface locations an pertinent to this work.)* 0 p.m. 11/08/81 5/8" 24# J-55 Casing. w/500 sx. Hal-lite w/ 1/4#/sx. x 2% CaCl followed by 200 sx. 1 ciruclation through out job.</pre>
17. DESCRIBE PRC including estim measured and t 11/08.81	POSED OR COMPLETED OPERATIONS (Cleated date of starting any proposed work. If firme vertical depths for all markers and zones Spud 12 1/4" hole @ 3:3 Ran 36' Jts. (1500') 8 Set @ 1495'. Cemented Flocele, 5# Gilsonite/s Class "C" 2% CaCl. Ful	<pre>GICAL SURVEY VEW MEXICO arly state all pertinent details, and give pertinent date well is directionally drilled, give subsurface locations an pertinent to this work.)* 0 p.m. 11/08/81 5/8" 24# J-55 Casing. w/500 sx. Hal-lite w/ 1/4#/sx. x 2% CaCl followed by 200 sx.</pre>
17. DESCRIBE PRC including estim measured and t 11/08.81	POSED OR COMPLETED OPERATIONS (Cleated date of starting any proposed work. If firme vertical depths for all markers and zones Spud 12 1/4" hole @ 3:3 Ran 36' Jts. (1500') 8 Set @ 1495'. Cemented Flocele, 5# Gilsonite/s Class "C" 2% CaCl. Ful	<pre>GICAL SURVEY VEW MEXICO arly state all pertinent details, and give pertinent date well is directionally drilled, give subsurface locations an pertinent to this work.)* 0 p.m. 11/08/81 5/8" 24# J-55 Casing. w/500 sx. Hal-lite w/ 1/4#/sx. x 2% CaCl followed by 200 sx. 1 ciruclation through out job.</pre>
17. DESCRIBE PRC including estim measured and t 11/08.81	POSED OR COMPLETED OPERATIONS (Cleated date of starting any proposed work. If firme vertical depths for all markers and zones Spud 12 1/4" hole @ 3:3 Ran 36' Jts. (1500') 8 Set @ 1495'. Cemented Flocele, 5# Gilsonite/s Class "C" 2% CaCl. Ful	<pre>GICAL SURVEY VEW MEXICO arly state all pertinent details, and give pertinent date well is directionally drilled, give subsurface locations an pertinent to this work.)* 0 p.m. 11/08/81 5/8" 24# J-55 Casing. w/500 sx. Hal-lite w/ 1/4#/sx. x 2% CaCl followed by 200 sx. 1 ciruclation through out job.</pre>
17. DESCRIBE PRC including estim measured and t 11/08.81	POSED OR COMPLETED OPERATIONS (Cleated date of starting any proposed work. If firme vertical depths for all markers and zones Spud 12 1/4" hole @ 3:3 Ran 36' Jts. (1500') 8 Set @ 1495'. Cemented Flocele, 5# Gilsonite/s Class "C" 2% CaCl. Ful	<pre>GICAL SURVEY VEW MEXICO arly state all pertinent details, and give pertinent date well is directionally drilled, give subsurface locations an pertinent to this work.)* 0 p.m. 11/08/81 5/8" 24# J-55 Casing. w/500 sx. Hal-lite w/ 1/4#/sx. x 2% CaCl followed by 200 sx. 1 ciruclation through out job.</pre>
17. DESCRIBE PRC including estim measured and t 11/08.81 11/08/81	POSED OR COMPLETED OPERATIONS (Cleated date of starting any proposed work. If strue vertical depths for all markers and zones Spud 12 1/4" hole @ 3:3 Ran 36' Jts. (1500') 8 Set @ 1495'. Cemented Flocele, 5# Gilsonite/s Class "C" 2% CaCl. Ful Circulated 25 sx. to su	<pre>GICAL SURVEY MEXICO arly state all pertinent details, and give pertinent date well is directionally drilled, give subsurface locations an pertinent to this work.)* 0 p.m. 11/08/81 5/8" 24# J-55 Casing. w/500 sx. Hal-lite w/ 1/4#/sx. x 2% CaCl followed by 200 sx. 1 ciruclation through out job. rface. P.O.B. @ 7:52 a.m. 11/1</pre>
17. DESCRIBE PRC including estim measured and t 11/08.81 11/08/81 Subsurface Safety V	POSED OR COMPLETED OPERATIONS (Cleated date of starting any proposed work. If strue vertical depths for all markers and zones Spud 12 1/4" hole @ 3:3 Ran 36' Jts. (1500') 8 Set @ 1495'. Cemented Flocele, 5# Gilsonite/s Class "C" 2% CaCl. Ful Circulated 25 sx. to su	<pre>GICAL SURVEY MEXICO arly state all pertinent details, and give pertinent date well is directionally drilled, give subsurface locations an pertinent to this work.)* 0 p.m. 11/08/81 5/8" 24# J-55 Casing. w/500 sx. Hal-lite w/ 1/4#/sx. x 2% CaCl followed by 200 sx. 1 ciruclation through out job. rface. P.O.B. @ 7:52 a.m. 11/1 Set @ Set @</pre>
17. DESCRIBE PRC including estim measured and t 11/08.81 11/08/81 Subsurface Safety V	POSED OR COMPLETED OPERATIONS (Cleated date of starting any proposed work. If strue vertical depths for all markers and zones Spud 12 1/4" hole @ 3:3 Ran 36' Jts. (1500') 8 Set @ 1495'. Cemented Flocele, 5# Gilsonite/s Class "C" 2% CaCl. Ful Circulated 25 sx. to su	<pre>GICAL SURVEY MEXICO arly state all pertinent details, and give pertinent date well is directionally drilled, give subsurface locations an pertinent to this work.)* 0 p.m. 11/08/81 5/8" 24# J-55 Casing. w/500 sx. Hal-lite w/ 1/4#/sx. x 2% CaCl followed by 200 sx. 1 ciruclation through out job. rface. P.O.B. @ 7:52 a.m. 11/1 Set @ Set @</pre>
 17. DESCRIBE PRC including estim measured and t 11/08.81 11/08/81 Subsurface Safety Vi 18. I hereby certify t 	POSED OR COMPLETED OPERATIONS (Cleated date of starting any proposed work. If strue vertical depths for all markers and zones Spud 12 1/4" hole @ 3:3 Ran 36' Jts. (1500') 8 Set @ 1495'. Cemented Flocele, 5# Gilsonite/s Class "C" 2% CaCl. Ful Circulated 25 sx. to su	<pre>GICAL SURVEY VEW MEXICO arly state all pertinent details, and give pertinent date: well is directionally drilled, give subsurface locations an pertinent to this work.)* 0 p.m. 11/08/81 5/8" 24# J-55 Casing. w/500 sx. Hal-lite w/ 1/4#/sx. x 2% CaCl followed by 200 sx. 1 ciruclation through out job. rface. P.O.B. @ 7:52 a.m. 11/1 </pre>
 17. DESCRIBE PRC including estim measured and t 11/08.81 11/08/81 Subsurface Safety Value 11.108/81 	A Test & other. POSED OR COMPLETED OPERATIONS (Cleated date of starting any proposed work. If true vertical depths for all markers and zones Spud 12 1/4" hole @ 3:3 Ran 36' Jts. (1500') 8 Set @ 1495'. Cemented Flocele, 5# Gilsonite/s Class "C" 2% CaCl. Ful Circulated 25 sx. to su alve: Manu. and Type that the foregoing is true and correct NREE, TILE Wester:	GICAL SURVEY MEXICO arly state all pertinent details, and give pertinent date: well is directionally drilled, give subsurface locations an pertinent to this work.)* 0 p.m. 11/08/81 5/8" 24# J-55 Casing. w/500 sx. Hal-lite w/ 1/4#/sx. x 2% CaCl followed by 200 sx. 1 ciruclation through out job. rface. P.O.B. @ 7:52 a.m. 11/1 Set @F Agents for n_Reserveoste
17. DESCRIBE PRC including estim measured and t 11/08.81 11/08/81 Subsurface Safety Vi 18. I hereby certify t	A Test & other. POSED OR COMPLETED OPERATIONS (Cleated date of starting any proposed work. If true vertical depths for all markers and zones Spud 12 1/4" hole @ 3:3 Ran 36' Jts. (1500') 8 Set @ 1495'. Cemented Flocele, 5# Gilsonite/s Class "C" 2% CaCl. Ful Circulated 25 sx. to su alve: Manu. and Type that the foregoing is true and correct NREE, TITLE Wester R A CHAPMAN This space for Federal or	GICAL SURVEY VEW MEXICO arly state all pertinent details, and give pertinent date: well is directionally drilled, give subsurface locations an pertinent to this work.)* 0 p.m. 11/08/81 5/8" 24# J-55 Casing. w/500 sx. Hal-lite w/ 1/4#/sx. x 2% CaCl followed by 200 sx. 1 ciruclation through out job. rface. P.O.B. @ 7:52 a.m. 11/1 State office use)
17. DESCRIBE PRC including estim measured and t 11/08.81 11/08/81 Subsurface Safety Va 18. I hereby certify t	A Test & other. POSED OR COMPLETED OPERATIONS (Cleated date of starting any proposed work. If true vertical depths for all markers and zones Spud 12 1/4" hole @ 3:3 Ran 36' Jts. (1500') 8 Set @ 1495'. Cemented Flocele, 5# Gilsonite/s Class "C" 2% CaCl. Ful Circulated 25 sx. to su alve: Manu. and Type that the foregoing is true and correct NREE, TITLE Wester R A CHAPMAN This space for Federal or	GICAL SURVEY MEXICO arly state all pertinent details, and give pertinent date: well is directionally drilled, give subsurface locations an pertinent to this work.)* 0 p.m. 11/08/81 5/8" 24# J-55 Casing. w/500 sx. Hal-lite w/ 1/4#/sx. x 2% CaCl followed by 200 sx. 1 ciruclation through out job. rface. P.O.B. @ 7:52 a.m. 11/1 Set @F Agents for n_Reserveoste
17. DESCRIBE PRC including estim measured and t 11/08.81 11/08/81 Subsurface Safety Va 18. I hereby certify t SIGNED ROUT APPROVED BY	A Test & other. POSED OR COMPLETED OPERATIONS (Cleated date of starting any proposed work. If true vertical depths for all markers and zones Spud 12 1/4" hole @ 3:3 Ran 36' Jts. (1500') 8 Set @ 1495'. Cemented Flocele, 5# Gilsonite/s Class "C" 2% CaCl. Ful Circulated 25 sx. to su alve: Manu. and Type that the foregoing is true and correct NREE, TITLE Wester: R A CHAPMAN (This space for Federal or TITLE WAT 12 1/4" hole @ 3:3 Ran 36' Jts. (1500') 8 Set @ 1495'. Cemented Flocele, 5# Gilsonite/s Class "C" 2% CaCl. Ful Circulated 25 sx. to su TITLE Wester: R A CHAPMAN (This space for Federal or TITLE WAT 12 1981	GICAL SURVEY VEW MEXICO arly state all pertinent details, and give pertinent date: well is directionally drilled, give subsurface locations an pertinent to this work.)* 0 p.m. 11/08/81 5/8" 24# J-55 Casing. w/500 sx. Hal-lite w/ 1/4#/sx. x 2% CaCl followed by 200 sx. 1 ciruclation through out job. rface. P.O.B. @ 7:52 a.m. 11/1 State office use)
17. DESCRIBE PRC including estim measured and t 11/08.81 11/08/81 Subsurface Safety Va 18. I hereby certify to SIGNED RCGF APPROVED BY	POSED OR COMPLETED OPERATIONS (Cleated date of starting any proposed work. If strue vertical depths for all markers and zones Spud 12 1/4" hole @ 3:3 Ran 36' Jts. (1500') 8 Set @ 1495'. Cemented Flocele, 5# Gilsonite/s Class "C" 2% CaCl. Ful Circulated 25 sx. to su alve: Manu. and Type that the foregoing is true and correct NREE, TITLE Wester: RACHAPMAN (This space for Federal or CAT 17981	GICAL SURVEY VEW MEXICO arly state all pertinent details, and give pertinent date: well is directionally drilled, give subsurface locations an pertinent to this work.)* 0 p.m. 11/08/81 5/8" 24# J-55 Casing. w/500 sx. Hal-lite w/ 1/4#/sx. x 2% CaCl followed by 200 sx. 1 ciruclation through out job. rface. P.O.B. @ 7:52 a.m. 11/1 State office use)
17. DESCRIBE PRC including estim measured and t 11/08.81 11/08/81 Subsurface Safety Va 18. I hereby certify to SIGNED RCGF APPROVED BY	A Test & other. POSED OR COMPLETED OPERATIONS (Cleated date of starting any proposed work. If true vertical depths for all markers and zones Spud 12 1/4" hole @ 3:3 Ran 36' Jts. (1500') 8 Set @ 1495'. Cemented Flocele, 5# Gilsonite/s Class "C" 2% CaCl. Ful Circulated 25 sx. to su alve: Manu. and Type that the foregoing is true and correct NREE, TITLE Wester R A CHAPMAN This space for Federal or	GICAL SURVEY VEW MEXICO arly state all pertinent details, and give pertinent date: well is directionally drilled, give subsurface locations an pertinent to this work.)* 0 p.m. 11/08/81 5/8" 24# J-55 Casing. w/500 sx. Hal-lite w/ 1/4#/sx. x 2% CaCl followed by 200 sx. l ciruclation through out job. rface. P.O.B. @ 7:52 a.m. 11/1



. . . RECEIVED DEC **21 1981**,

TO CONSERVATION D'V