

OIL CONSERVATION DIVISION

P. O. BOX 2086

SANTA FE, NEW MEXICO 87501

Form O-100
Revised 10-1-77

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

1a. Indicate Type of Lease
State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
1b. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.

OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
Name of Operator: Cibola Energy Corporation
Address of Operator: P.O. Box 1668, Albuquerque, New Mexico 87103
Location of Well: UNIT LETTER <u>J</u> <u>1980</u> FEET FROM THE <u>South</u> LINE AND <u>1980</u> FEET FROM THE <u>East</u> LINE, SECTION <u>7</u> TOWNSHIP <u>9S</u> RANGE <u>30E</u> N.M.P.M.

7. Unit Agreement Name
8. Term of Lease (Date)
9. Well No. 1
10. Field and Pool, or Vicinity Cato San Andres
11. Elevation (Show whether DF, RT, GR, etc.) 4019.5
12. County Chaves

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Cut and pulled 2608' of 4 1/2" casing.

1st plug, 25 sacks Class C Cement, pumped at 3220' tagged at 3074'.
2nd plug, 40 sacks Class C Cement, pumped at 2650' tagged at 2539'.
3rd plug, 40 sacks Class C Cement, pumped at 2300' tagged at 2100'.
4th plug, 40 sacks Class C Cement, pumped at 2046' top estimated at 1900'.
5th plug, 40 sacks Class C Cement, pumped at 1350' top estimated at 1200'.
6th plug, 40 sacks Class C Cement, pumped at 310' tagged at 180'.
Surface 10 sacks with dry hole marker.

Location will be cleared of junk and leveled by 6-15-83.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Quinta P. Vigil</u>	TITLE <u>Drilling Secretary</u>	DATE <u>4-6-83</u>
APPROVED BY <u>Billy E. Pruhue</u>	TITLE _____	DATE <u>AUG 24 2001</u>
CONDITIONS OF APPROVAL IF ANY:		

RECEIVED
APR 8 1983
O.G.D.
HOBBS OFFICE