

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

N. M. OIL CONS. COMMISSION  
P. O. BOX 1980  
HOBBS, NEW MEXICO 88240

CASE NM-04 3-A	
MAN, ALLOTTEE OR TRIBE NAME	
7. UNIT AGREEMENT NAME	
8. FARM OR LEASE NAME MILLER <del>FEDERAL</del> 33 <i>Federal</i>	
9. WELL NO. 2	
10. FIELD OR WILDCAT NAME TOM TOM	
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA SEC. 33, 7S, 31 E	
12. COUNTY OR PARISH CHAVES	13. STATE NEW MEXICO
14. API NO.	
15. ELEVATIONS (SHOW DF, KDB, AND WD) GR 4290.0	

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 5-331-C for such proposals.)

1. oil ☒ well ☒ gas well ☐ other

2. NAME OF OPERATOR  
UNION TEXAS PETROLEUM CORPORATION

3. ADDRESS OF OPERATOR  
1300WILCO BLDG, MIDLAND, TEXAS 79701

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1980 FSL and 1980 FEL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>
(other) <u>Drilling</u>	

(NOTE: Report results of multiple completion or zone change on Form 5-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

- 1) Drilling to 1-20-82. Drilling 7-7/8" hole to 3950'.
- 2) 1-21-82 Ran 5-1/2 to 3950'. DV Tool at 1547'. Cement with 425 sks. Ran temp. survey. Top of cement 1430'. Change out wellhead. Cut 5-1/2" and nipple up. Release rig 1-22-82
- 3) 1-23-82 thru 1-27-82 moving out rig. Cleaning up location.
- 4) 1-28-82 Waiting of service unit for completion.

RECEIVED  
FEB 2 1982

OIL & GAS  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Billie Hood TITLE REGULATORY ANALYST DATE 1-29-82

(This space for Federal or State office use)

TO BE FILED FOR RECORD  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

FEB 13 1982

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

See Instructions on Reverse Side