FRACTURE TREAT SHOOT OR ACIDIZE

PULL OR ALTER CASING MULTIPLE COMPLETE

REPAIR WELL

NM OIL CONS. CCMMISSION Drawer DD Artesia, NM 88210

Form Approved. Budget Bureau No. 42-R1424

or zone

LINITED STATES DEPAR

DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY	5. LEASE NM-15314 6. IF INDIAN, ALLOTTEE OR TRIBE NAME 7. UNIT AGREEMENT NAME		
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a wife reservoir. Use Form 9-331-C for such proposals.)			
1. oil 🖼 gas 🖂 MAV .	8. FARM OR LEASE NAME Yates Food 29 Jel		
2 NAME OF OPERATOR	9. WELL NO. 1		
Forister & Sweatt O. C. D. 3. ADDRESS OF OPERATOR ARTESIA OFFICE	10. FIELD OR WILDCAT NAME SE Chaves Queen Assoc.		
PO Box 161, Artesia, NM 88210 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec 29 T12S R31E 12. COUNTY OR PARISH 13. STATE Chaves New Mexico		
AT SURFACE: 990 FSL 1650 FWL AT TOP PROD. INTERVAL: AT TOTAL DEPTH:			
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	14. API NO.		
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 4068.7		
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF			

(NOTE: Report results of in

CHANGE ZONES 1982 ABANDON* casing (other) OIL & GAS GECLOGICAL SURVEY 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and veixe pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and

- Spudded 12% hole at 10:00 P.M. March 30, 1982. Drilled to Ran 25 jts 990' 8 5/8 23# casing set at 1002'. Cemented with 375 sx Hal Lite with 2% Cal Clor and 100 sx Class C with 2% Cal Clor. Plug down 11:30 P.M. March 31, 1982. Cement circulated.
- Drilled 7 7/8" hole to 2620'. Ran 67 jts 2651' $4\frac{1}{2}$ 9.5# casing set at 2620'. Cemented with 275 sx 50/50 Poz mix with 6# salt and 3/10% CFR2. Plug down 9:00 P.M. 4/5/82.

measured and true vertical depths for all markers and zones pertinent to this work.)*

Subsurface Safety Valve: Manu. and Ty	pe		Set @ Ft.
18. I hereby/certify that the foregoing i	s true and correct		
SIGNED HELLEY TO A	Partner Partner	DATE _	4/7/82
	(This space for Federal or State office us	se)	
APPROVED BYCONDITIONS OF APPROVAL, IF ANY:	TITLE	DATE	ACCEPTED FOR RECORD
			MAY 1 2 1982
	*See Instructions on Reverse Side		U.S. GEOLOGICAL SURVEY ROSWELL, NEW MEXIC

.

MAY 19 1982

Husas Office