

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

N. M. OIL CO. COMMISSION

P. O. BOX 1980

HOBBS, NEW MEXICO 88240

Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

NM 18041

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

East White Ranch Deep

9. WELL NO.

1

10. FIELD AND TOOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR R.R. AND
SURVEY OR AREA

Sec 14-T13S-R30E

12. COUNTY OR PARISH 13. STATE

Chaves

NM

SUNDRY NOTICES AND REPORTS ON WELLS
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR
Gulf Oil Corporation

3. ADDRESS OF OPERATOR
P. O. Box 670, Hobbs, NM 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

660' FSL & 1980' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3926' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Casing

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)

GIH open-ended to 4390'. Spot 150 sacks Class "C" with CaCl₂. WOC. Tag cement at 4105'. Spot 150 sacks Class "C" with CaCl₂. WOC. Tag cement at 3498'. Dr1 cement. TD 12:00 P.M., 7-31-82; logs complete 6:30 A.M., 8-2-82. RU & ran 96 joints 5 1/2" 17# N-80 Class "B", 69 joints 17# K-55 Class "B" and 101 + 1 cut joint 17# K-55 Class "A", set at 10,600'. Cement with 500 sacks 50/50 poz. Plug down 11:30 P.M., 8-3-82. WOC 18 hours. Temperature survey top of cement 8875'. Test casing 2000#, ok.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Area Drilling Superintendent

DATE 8-30-82

(This space for Federal

ACCEPTED FOR RECORD

APPROVED BY (ORIG. SGD.) DAVID R. GLASS

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

OCT 12 1982

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

Instructions on Reverse Side