

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. O. Jon
P.O. 1980
Hobbs, NM 88241
Under ROW NM 53889

FORM APPROVED
Budget Bureau No. 1004 0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well
☐ Oil Well ☐ Gas Well ☒ Other SWD

2. Name of Operator
YATES PETROLEUM CORPORATION (505) 748-1471

3. Address and Telephone No.
105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
1980' FNL & 1980' FWL of Section 12-T8S-R31E (Unit F, SENW)

5. Lease Designation and Serial No.

6. If Indian, Allottee or Tribe Name

7. If Unit or C.A. Agreement Designation

8. Well Name and No.

Champlin UL Federal

9. API Well No.

1

10. Field and Pool, or Exploratory Area

SWD - San Andres

11. County or Parish, State

Chaves Co., NM

12 CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Clean Out

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form 1)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Propose to clean out well as follows:

1. Nipple 'up BOP. Release Baker Model R packer. TOOH with plastic coated tubing and packer. TIH with bit and scraper. Clean out fill to 4200'± with produced water. TOOH with bit & scraper.
2. TIH with treating packer and set at 3990'. (NOTE: Perforations are 4009-4217'). Pump 500 gallons xylene followed with 6000 gallons 15% iron control HCL acid with 2 gpt premium non-emulsifier with ball sealers.
3. Pump step rate test with produced water.
4. TIH with plastic coated tubing and nickel plated packer. Return to injection.

NOTIFY BLM-ROSWELL (505-627-0272) AND OCD-HOBBS (505-393-6161) IN SUFFICIENT TIME TO WITNESS MECHANICAL INTEGRITY TEST

14. I hereby certify that the foregoing is true and correct

Signed

Rusty Klein

Title Operations Technician

Date Dec. 10, 1997

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

SUBJECT TO LIKE
APPROVAL BY STATE

APPROVED
PETER W. BLISS

Date

DEC 16 1997

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side