

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐ **DEC 2 1982**

2. NAME OF OPERATOR
Exxon Corporation

3. ADDRESS OF OPERATOR
P.O. Box 1600, Midland, TX 79702

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660' FSL and 1980' FEL of Section
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input checked="" type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>
(other) <input type="checkbox"/>	<input type="checkbox"/>

5. LEASE
NM - 055564

6. IF INDIAN, ALLOTTEE OR TRIBE NAME
--

7. UNIT AGREEMENT NAME
--

8. FARM OR LEASE NAME
Isler Federal

9. WELL NO.
4

10. FIELD OR WILDCAT NAME Undesignated
Many Gates ABO

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 30, T-9-S, R-30-E

12. COUNTY OR PARISH Chaves

13. STATE
New Mexico

14. API NO.
30-005-20418

15. ELEVATIONS (SHOW DF, KDB, AND WD)
4046

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 17 1/2" hole 2:15 a.m. 10-20-82. T.D. 417'.
Ran 10 joints 13 3/8" 54.5# K-55 casing set at 411'. Cement w/500
sx Class "C" wt. 14.6, 2% CaCl. Bump plug at 3:45 p.m. 10-21-82.
Circulated 170 sx. WOC.
Tested 13 3/8" casing at 8:15 p.m. 10-23-82 w/1500# - held OK.
Drilled cement and plug at 8:15 p.m. 10-23-82.
Drilling.

* Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED David R. Glass TITLE Sr. Administrator DATE 11-24-82

ACCEPTED FOR RECORD

(This space for Federal or State office use)

(ORIG. SGD.) DAVID R. GLASS

APPROVED BY _____ DATE _____

CONDITIONS OF APPROVAL _____

MINERALS MANAGEMENT SERVICE
ROSWELL, NEW MEXICO

RECEIVED
NOV 30 1982

RECEIVED
DEC 3 1982
FBI
NEW YORK OFFICE