

U. S. OIL CONS. COMMISSION
UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
NEW MEXICO

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR
Forister & Sweatt

3. ADDRESS OF OPERATOR
PO Box 161, Artesia, NM 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 990 FNL 1650 FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) casing and testing

5. LEASE

NM 16819

6. NAME OF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Ivey Lynne Federal

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Chaves Queen SE Assoc.

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 5 T13S R31E

12. COUNTY OR PARISH

Chaves

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
4059.8 GR

(NOTE: Report results of multiple completion or zone change on Form 9-331-C)

RECEIVED

NOV 3 1982

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Resume drilling operations 6:15 p.m. Oct. 24, 1982.
2. Drilled 12 1/4" hole to 975'. Ran 24 jts 962' of 23# 8 5/8 casing set at 974'. Cemented with 375 sx HalliLite with 2% CaCl. 1/2# Flocele followed with 100 sx Class C with 2% ClClor. Circulated 90 sx to pit. Plug down 12:30 p.m. 10-25-82.
3. Drilled 7 7/8" hole to 2532'. Cored and D.S.T. Queen formation from 2532 to 2553'.
4. Drilled 7 7/8" hole to 2650'. Ran 22 jts 858' 4 1/2" 10.5# and 46 jts 1820' 9.5# 4 1/2" casing. Tot 2678' set at 2650'. Cemented with 300 sx Class C 50/50 Poz with 2% gel 6# salt per sack 3% CFR. Plug down 12:00 a.m. 10-29-82. Cement top at 1750'.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

David R. Glass

TITLE

Partner

DATE

11-1-82

(ORIG. SGD.)

DAVID R. GLASS

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL

NOV 3 1982

TITLE

DATE

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

See Instructions on Reverse Side

RECEIVED

NOV 4 1982

O.C.D.
HOBBS OFFICE