

UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
NM OIL CONS. COMM. 701
SUBMIT IN THIS DRAWER (Other instructions on reverse side)
Artesia, NM 88210

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-19611

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

McClellan Federal *Com*

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

12. COUNTY OR PARISH

Chaves

13. STATE

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Hilliard Oil & Gas, Inc.

3. ADDRESS OF OPERATOR

3000 North Garfield Suite 120 Midland, TX 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface

2180' FSL and 660' FEL Section 27 Township 15S Range 30E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4071' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) spudding & setting surface casing

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

The above referenced well was spudded at 7:30 pm 11-28-82. 20" conductor pipe had been set at 40' and cemented.

13-3/8" casing was run and cemented as follows:

1 Guideshoe	1.50'-1 centralizers
1 Jt 13-3/8" 48#H-40 ST&C	40.42'
Insert Float	-
11 jts 13-3/8" 48# H-40 ST&C	466.70'-5 centralizers
	508.62'
Feet above rotary	9.62'
Casing set @	499.00'

Halliburton services pumped the following cement: 525sx "C" + 2% CaCl₂ 150sx of cement was circulated.

RECEIVED

JAN 21 1983

OIL & GAS

MINERALS MANAGEMENT SERVICE

ROSWELL, NEW MEXICO

DATE

18. I hereby certify that the foregoing is true and correct

SIGNED

Robert E. Patterson
Robert E. Patterson

TITLE Drilling Engineer

(This space for Federal or State office use)

(ORIG. SGD.) DAVID R. GLASS

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

JAN 24 1983

TITLE

DATE

MINERALS MANAGEMENT SERVICE
ROSWELL, NEW MEXICO

See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE : 1963 - O-485229

847 - 485

RECEIVED
JAN 26 1983
O.C.D.
MOBBS OFFICE