MM OIL CONS.	COMMISSION RECEIVED BY
Form 9-831 Drawer DD	Form Approved.
Dec. 1973 UNITED STATES Artesia, FM	SCALO Budget Bureau No. 42-81424 5. LEASE JUN 28 1984
DEPARTMENT OF THE INTERIOR	NM 067707 O. C. D.
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME SIA, OFFICE
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different	7. UNIT AGREEMENT NAME
reservoir. Use Form 9-331-C for such proposals.)	8. FARM OR LEASE NAME Siete-Federal
well well other	9. WELL NO.
2. NAME OF OPERATOR	#2
Petroleum Exploration Company, Inc.	10. FIELD OR WILDCAT NAME Siete-San Andres
3. ADDRESS OF OPERATOR P.O. BOX 809 ROSWell, NM 88201	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA Sec. 17 T8S,R31E
below.) AT SURFACE 1980' FNL & 660' FEL	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: Same AT TOTAL DEPTH: Same	Chaves NM
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE.	14. API NO.
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 42101 GL
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	
FRACTURE TREAT	
REPAIR WELL	(NOTE: Report Asylts of multiple completion or zone
PULL OR ALTER CASING	change on Ebon 9-330.)
MULTIPLE COMPLETE	
ABANDON• X	$\sim 10^{-10}$ $\sim 10^{-10}$
(other)	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Petroleum Exploration Company, Inc. requests permission to plug and abandon the above referenced well under current downhole conditions as follows:	
T.D 3789'	
Top of Fish - 3216'	OF LAND VIANA
Top of San Andres - 3015'	P OF WED CE
8 5/8" Casing set at - 367'	AN MUULITLU T
Base of Salt - 1800'	
1) Set 40 sack cement plug at 1800' - 1900'	JUN 20 1984
2) Set 40 sack cement plug at 300' - 450'	
3) Set 10 sack cement plug at surface	B. DISL & N. M. J. P.
4) Install Dry Hole Marker Subsurface Safety Valve: Manu. and Type	Set @
18. I hereby certify that the foregoing is true and correct	
signed wally brakan TITLE Sec/Tres DATE 6/15/84	
APPROVED (This space for Federal or State office use)	
APPROVED AY DATE DATE	
JUN 27 1981	
*See Instructions on Reverse Si	de

.

A CALLER AND

......

. RECEIVED JUN 2.9 1984 HONES CFFICE

**.** 

• • • • • • •

1