APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

## NM CIL COMS. COMMISSION

Drawer DD

Form Approved. Budget Bureau No. 42-R1424

## UNITED STATES tesia. NM 88210

DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

5.	LEASE	
	NM -	067707
6	IF INDIA	N ALLOTTEE OR TRIBE NAME

GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME	
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME Siete-Federal	AUG 0 9 1983
1. oil gas other	9. WELL NO.	Q, C, D.
2. NAME OF OPERATOR	2-Y	ARTESIA, OFFICE
Petroleum Exploration Company, Inc.	10. FIELD OR WILDCAT NAME	, , , , , , , , , , , , , , , , , , , ,
3. ADDRESS OF OPERATOR	Siete-San Andres	
P.O. Box 809, Roswell, New Mexico 88201	11. SEC., T., R., M., OR BLK. AN	ID SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA	21 F N M D M
helow)	Sec. 17, T-8-S, R-	
AT SURFACE: 1980' FNL & 610' FEL	12. COUNTY OR PARISH 13. S	
AT TOP PROD. INTERVAL: Same		Mexico
AT TOTAL DEPTH: Same	14. API NO.	
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,		
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, K	DB AND (D)
	4210.4 GR 42	21825B
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:		±_ − ¬
TEST WATER SHUT-OFF		<u> </u>
FRACTURE TREAT		<u> </u>
SHOOT OR ACIDIZE	(NOTE: Report results of multiple c	omidie Tion or Ozone
REPAIR WELL  PULL OR ALTER CASING	change on Form 9-330.)	—ix □
MULTIPLE COMPLETE		
CHANGE ZONES		
ABANDON <sup>¢</sup> □		<u></u>
(other) Surface Casing		
<ol> <li>DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stational including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertined.)</li> </ol>		pertinent dates, e locations and
7-20-83 Spudded 12 1/4" hole at 10:00 A.M.	•	
7-21-83 Drilled to 1130'. Ran 1141.98' or	f = 8.5/8". $24$ # casing and	d
7-21-83 Drilled to 1130'. Ran 1141.98' of set at 1128.26' K.B.M. Cemented v	with 475 sx. Halliburt	on
lite 2% C.C. and 100 sx class "C"	with 2% C.C. cement	
lite 2% U.U. and 100 SX class of	M	
circulated - plug down at 4:15 P	• 111 •	
7-22-83 After W.O.C. for 18 hours, pressur (30) minutes - Held OK. Started	re up to 1000# for thir drilling out shoe at 10	ty :15 A.M.
	0.4.0	E+
Subsurface Safety Valve: Manu. and Type	Set (@ = -	г.
18. I hereby certify that the foregoing is true and correct		
Vice-Presi	dent DATE July 25.	1983

\*See Instructions on Reverse Side

(This space for Federal or State office use)

.... DATE \_\_

CEPTED TON ...

ROSWELL, NEW MEXICO

RECEIVED

AUG 1 2 1983

HOBBS OFFICE

\***0**53**\*** 25 6 34 5 36 5

State of the state