

UNITED STATES  
 DEPARTMENT OF THE INTERIOR  
 GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐  
 2. NAME OF OPERATOR  
 BISON PETROLEUM CORPORATION  
 3. ADDRESS OF OPERATOR  
 203 W. 8th #510 Amarillo, TX 79101  
 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
 AT SURFACE: 1980 FSL 1485 FWL Unit K  
 AT TOP PROD. INTERVAL:  
 AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input checked="" type="checkbox"/>
(other) <input type="checkbox"/>	

5. LEASE  
 NM-17226 A  
 6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
 7. UNIT AGREEMENT NAME  
 8. FARM OR LEASE NAME  
 WALTERS FEDERAL  
 9. WELL NO.  
 3  
 10. FIELD OR WILDCAT NAME  
 SE CHAVES QUEEN GAS AREA ASSO.  
 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
 Sec 34 T13S R30E  
 12. COUNTY OR PARISH 13. STATE  
 Chaves NM  
 14. API NO.  
 15. ELEVATIONS (SHOW DF, KDB, AND WD)  
 3863.2 G.R. 3870 K.B.

(NOTE: Report results of multiple completion zone change on Form 9-330.)

RECEIVED  
 DEC 22 10 51 AM '83  
 BUREAU OF LAND MANAGEMENT  
 ROSWELL DISTRICT

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

11-15-83 Pull & LD 83-5/8" rods, BH pump, 67 jts. 2 3/8" tbg, SN and Perf sub. Tag bottom @ 2157'. Pull to 2130' and spot 25 sx. cmt. (Perfs 2134-44')

11-16-83 Tag cmt plug @ 1886'. Displace hole w/gel water. Recovered 17 jts. 8 5/8" csg. Spot 50 sx. cmt @ 682'.

11-17-83 Tag TOC @ 434'. Spot 25 sx @ 93' and 5 sx. at surface. Welded on plate and installed marker.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Peter W. Chester TITLE President DATE 12-20-83

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
 CONDITIONS OF APPROVAL, IF ANY:

APPROVED  
 PETER W. CHESTER  
 MAY 30 1985  
 BUREAU OF LAND MANAGEMENT  
 ROSWELL RESOURCE AREA