

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐  
 well well  
 2. NAME OF OPERATOR  
 Petroleum Exploration Co., Inc.  
 3. ADDRESS OF OPERATOR  
 P.O. Box 809, Roswell, NM 88201  
 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
 AT SURFACE: 660' FWL & 660' FNL  
 AT TOP PROD. INTERVAL: Same  
 AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

## REQUEST FOR APPROVAL TO:

## SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐  
 FRACTURE TREAT ☐  
 SHOOT OR ACIDIZE ☐  
 REPAIR WELL ☐  
 PULL OR ALTER CASING ☐  
 MULTIPLE COMPLETE ☐  
 CHANGE ZONES ☐  
 ABANDON\* ☐  
 (other) ☐

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☒

5. LEASE  
 NM 19197  
 6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
 -  
 7. UNIT AGREEMENT NAME  
 -  
 8. FARM OR LEASE NAME  
 Phillips - Federal  
 9. WELL NO.  
 #1  
 10. FIELD OR WILDCAT NAME  
 Tom-Tom San Andres  
 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
 Sec. 10, T8S-R31E  
 12. COUNTY OR PARISH  
 Chaves  
 13. STATE  
 NM  
 14. API NO.  
 -  
 15. ELEVATIONS (SHOW DF, KDB, AND WD)  
 4283 GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

8-21-84 MIRUPU, Tripped rods out of hole and laid down rods.

8-22-84 Pulled 119 jts. of 2 3/8" tubing (3848.72') out of hole. Ran in hole with cast iron bridge plug, 117 jts 2 3/8" tubing. Set at 3797.04'. Displaced casing with plugging mud (64 bbls water, 18 sacks gel). Set 60' cement plug from 3797'-3737'. Pulled out of hole. Perforated 4 1/2" casing with 2 shots at 1300'. Ran in hole with cast iron cement retainer and 37 jts of 2 3/8" tubing. Set at 1205'. Squeezed with 90 sxs. class "C" cement. Pulled out of hole; laid down tubing. Set 125' cement plug to surface. Installed dry hole marker. Laid Down, moved out pulling unit.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Wesley Bagley TITLE Secretary/Treasurer DATE 8-27-84

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

RECEIVED BY  
NOV 07 1984  
O. C. D.  
ARTESIA, OFFICE

RECEIVED  
NOV 13 1984  
HOBBS, OFFICE