NM OIL CONS.

DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY 5. LEASE N.M. 19197 6. IF INDIAN, ALLOTTEE OR TRIBE NAME 7. UNIT AGREEMENT NAME 8. FARM OR LEASE NAME Phillips-Federal 9. WELL NO. 1. Oil Well Well other 1. Oil Well Well other 2. NAME OF OPERATOR Petroleum Exploration Company, Inc. 3. ADDRESS OF OPERATOR P.O. Box 809, Roswell, N.M. 88202-080 4. JOCATION OF WELL (PEPORT LOCATION CLEARLY See space 17) 5. LEASE N.M. 19197 6. IF INDIAN, ALLOTTEE OR TRIBE NAME P. UNIT AGREEMENT NAME Phillips-Federal 9. WELL NO. 10. FIELD OR WILDCAT NAME Tom-Tom, San Andres P.O. Box 809, Roswell, N.M. 88202-080 911. SEC., T., R., M., OR BLK. AND SURVEY OR AREA	Form 9-331	Drawer DD Artesia, NM 88210	Form Approved. Budget Bureau No. 42R1424
SUNDERS NOTICES AND REPORTS ON WELLS (Do not use that form for proposals to drill or to despen or plug back to a different reservoir. Use from 3-31-1- for such proposals. In drill or to despen or plug back to a different reservoir. Use from 3-31-1- for such proposals. In drill or to despen or plug back to a different reservoir. Use from 3-31-1- for such proposals. In drill or to despen or plug back to a different reservoir. Use from 3-31-1- for such proposals. In drill or to despen or plug back to a different reservoir. Use from 3-31-1- for such proposals. In drill other 2. NAME OF OPERATOR PETCH CASTION COMPANY. In 1. O. I. O. S. ADDRESS OF OPERATOR POLICE REPORTATION COMPANY. In 1. O. S. ADDRESS OF OPERATOR POLICE. GROWN CONTINUED C	Dec. 1973	UNITED STATES 10	
SUNDRY NOTICES AND REPORTS ON WELLS (Co. not use this form for proposate to delide not beepen or plug back to a different sereour. Use from Post proposate to delide not beepen or plug back to a different sereour. Use from Post proposate to delide not beepen or plug back to a different sereour. Use from Post proposate to delide not beepen or plug back to a different sereour. Use from Post proposate to delide not beepen or plug back to a different sereour. Use from Post proposate to delide not beepen or plug back to a different sereour. Use from Post post proposate in the propos	ſ	DEPARTMENT OF THE INTERIOR	
SUBDRY NOTICES AND REPORTS OF WHITE AND IN PREFIXED TO A WELL NO. 1. of well S		-	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
1. well S gas other 2. NAME OF OPERATOR PETROLEUM EXPLORATION COMPANY, Inc. 3. ADDRESS OF OPERATOR P.O. Box 809, Roswell, N.M. 88202-080 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below). AT SURFACE: 660' FWL and 660' FNL AT TOP PROD. INTERVAL: SAME AT TOTAL DEFTH: SAME 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF SHOW Company of the policy o	SUNDRY	NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR Petroleum Exploration Company, Inc. 3. ADDRESS OF OPERATOR P.O. BOX 809, Roswell, N.M. 88202-08091. SCC. T.R. M., OR BLK. AND SURVEY OR AREA ALLOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below). AT SURFACE: 660' FWL and 660' FNL AT TOP PROD. INTERVAL: Same AT TOTAL DEFTH: Same 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all menters and tones pertinent to this work.) 10-10-83 Ran Schlumberger Cement Bond Log. Perforated: 3888, 3889, 3890, 3890.5, 3895, 3898, 3913, 3913.5, 3914, 3916, 3918, 3923, 3924, 3924.5, 3925.5, 3939.5, 3930, 3930.5, and 3931. Set 121 joints of 2-3/8", 4.6 S.T. & C., V-55, API Range 2 Tubing. Set Packer at 3787.01' 10. Intereby certify that the foregoing is true and correct signed. 10. THE SEC. INCL. DATE Set (1) - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -	(Do not use this for reservoir, Use Form	rm for proposals to drill or to deepen or plug back to a different 9–331—C for such proposals.)	8. FARM OR LEASE NAME
Petroleum Exploration Company, Inc. 3. ADDRESS OF OPERATOR P.O. BOX 809, Roswell, N.M. 88202-0809 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SUBFACE: 660' FWL and 660' FNL AT TOP PROD. INTERVAL: Same AT TOTAL DEFTH: Same 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT SHOTO OR ACIDIZE REPAIR WELL COMPLETE CHANGE ZONES ABANDON' (other) Completion Information 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally dilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 10-10-83 Ran Schlumberger Cement Bond Log. Perforated: 3888, 3889, 3890, 3890. 5, 3895, 3898, 3913, 3913. 5, 3914, 3916, 3918, 3923, 3924, 3924.5, 3925, 3925.5, 3939.5, 3930, 3930.5, and 3931. Set 121 joints of 2-3/8", 4.6 S.T. & C., V-55, API Range 2 Tubing. Set Packer at 3787.01' 10. FIELD OR WILLDAT NAME TOWN AND T	- IAI		
3. ADDRESS OF OPERATOR P.O. BOX 809, ROSWell, N.M. 89202-080 91. SEC. T. R. M. OR BLK. AND SURVEY OR A LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below) AT SURFACE: 660' FWL and 660' FNL AT TOP PROD. INTERVAL: Same 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE PRACTURE TREAT SHOOT OR ACIDIZE CHANGE ZONES ABANDON' (other) Completion Information 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 10-10-83 Ran Schlumberger Cement Bond Log. Perforated: 3888, 3889, 3890, 3890.5, 3895, 3898, 3913, 3913.5, 3914, 3916, 3918, 3923, 3924, 3924.5, 3925.5, 3939.5, 3930.5, 3894, 3916, 3918, 3923, 3924, 3924.5, 3925.5, 3939.5, 3930.5, 3894, 3916, 3918, 3918, 3913. Set 121 joints of 2-3/8", 4.6 S.T. & C., V-55, API Range 2 Tubing. Set Packer at 3787.01' APPRILL THE RECURBAN were for Entered or State office use). APPRILL THE RECURBAN were for Entered or State office use).	2. NAME OF C	PERATOR	1
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 660' FWL and 660' FNL AT 10P PROD. INTERVAL: SAME AT TOP PROD. INTERVAL: SAME AT TOP PROD. INTERVAL: SAME 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE PULL OR ALTER CASING WILLTIPLE COMPLETE CHANGE ZONES ABANDON- (other) Completion Information 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 10-10-83 Ran Schlumberger Cement Bond Log. Perforated: 3888, 3889, 3890, 3890.5, 3895, 3898, 3913, 3913.5, 3914, 3916, 3918, 3923, 3924, 3924.5, 3925.5, 3939.5, 3930, 3930.5, and 3931. Set 121 joints of 2-3/8", 4.6 S.T. & C., V-55, API Range 2 Tubing. Set Packer at 3787.01' Subsurface Safety Valve: Manu. and Type TITLE SAL INVAL. DATE (11-17-83) AND STATE Chaves New Mexico 14. API NO. 15. ELEVATIONS (SHOW DF, KDB, AND WD) 4283 GR, 4293.5 KB (NOTE: Report results of multiple completing or form with proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 10-10-83 Ran Schlumberger Cement Bond Log. Perforated: 3888, 3889, 3890, 3890.5, 3895, 3898, 3913, 3913.5, 3914, 3916, 3918, 3923, 3924, 3924.5, 3925.5, 3939.5, 3930, 3930.5, and 3931. Set 121 joints of 2-3/8", 4.6 S.T. & C., V-55, API Range 2 Tubing. Set Packer at 3787.01' Subsurface Safety Valve: Manu. and Type TITLE SAL INVAL. DATE (11-17-83) AND SARA SCHEMENT CONTRACTOR SIZE OFFICE USE.		F OPERATOR	Tom-Tom, San Andres
AS LOCATION WELL (REPORT BOOSTION CLEARCH: See State 17 below) AT SURFACE: 660' FWL and 660' FNL AT TOP PROD. INTERVAL: Same AT TOTAL DEPTH: Same AT TOTAL DEPTH: Same 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: 15. ELEVATIONS (SHOW DF, KDB, AND WD) 4283 GR, 4293.5 KB REPORT WATER SHUT-OFF FRACTURE TREAT 17. DESCRIBE PROPOSED OR COMPLETE COMPLETE OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 10-10-83 Ran Schlumberger Cement Bond Log. Perforated: 3888, 3889, 3890, 3890.5, 3895, 3898, 3913, 3913.5, 3914, 3916, 3918, 3923, 3924, 3924.5, 3925, 3939.5, 3930, 3930.5, and 3931. Set 121 joints of 2-3/8", 4.6 S.T. & C., V-55, API Range 2 Tubing. Set Packer at 3787.01' Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct SIGNED Jula South Title Sec. Low. 10-10-10-10-10-10-10-10-10-10-10-10-10-1			
AT SURFACE: 660' FWL and 660' FNL AT TOP PROD. INTERVAL: Same AT TOP PROD. INTERVAL: Same 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 17. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 18. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 19. CLEVATIONS (SHOW DF, KDB, AND WD) 4283 GR, 4293.5 KB 19. CLEVATIONS (SHOW DF, KDB, AND WD) 4283 GR, 4293.5 KB 19. CLEVATIONS (SHOW DF, KDB, AND WD) 4283 GR, 4293.5 KB 19. CLEVATIONS (SHOW DF, KDB, AND WD) 4283 GR, 4293.5 KB 10. CLEVATIONS (SHOW DF, KDB, AND WD) 4283 GR, 4293.5 KB 10. CLEVATIONS (SHOW DF, KDB, AND WD) 4283 GR, 4293.5 KB 10. CLEVATIONS (SHOW DF, KDB, AND WD) 4283 GR, 4293.5 KB 10. CLEVATIONS (SHOW DF, KDB, AND WD) 4283 GR, 4293.5 KB 10. CLEVATIONS (SHOW DF, KDB, AND WD) 4283 GR, 4293.5 KB 10. CLEVATIONS (SHOW DF, KDB, AND WD) 4283 GR, 4293.5 KB 10. CLEVATIONS (SHOW DF, KDB, AND WD) 4283 GR, 4293.5 KB 10. CLEVATIONS (SHOW DF, KDB, AND WD) 4283 GR, 4293.5 KB 10. CLEVATIONS (SHOW DF, KDB, AND WD) 4283 GR, 4293.5 KB 10. CLEVATIONS (SHOW DF, KDB, AND WD) 4283 GR, 4293.5 KB 10. CLEVATIONS (SHOW DF, KDB, AND WD) 4283 GR, 4293.5 KB 10. CLEVATIONS (SHOW DF, KDB, AND WD) 4283 GR, 4293.5 KB 10. CLEVATIONS (SHOW DF, KDB, AND WD) 4283 GR, 4293.5 KB 10. CLEVATIONS (SHOW DF, KDB, MCD, AND WD) 10. CLEVATIONS (SHOW DF, KDB, MCD, AND WD) 11. CLEVATIONS (SHOW DF, KDB, MCD, AND WD) 12. CLEVATIONS (SHOW DF, KDB, MCD, AND WD) 13. SET DATA (SHOW DF, KDB, MCD, AND WD) 14. API NO. 15. CLEVATIONS (SHOW DF, KDB, MCD, AND WD) 16. CLEVATIONS (SHOW DF, KDB, MCD, AND WD) 17. CLEVATIONS (SHOW DF, KDB, MCD, AND WD) 18. CLEVATIONS (SHOW DF, KDB, MCD, AND WD) 18. CLEVATIONS (SHOW DF, KDB, MCD, AND WD) 19. CLEVATIONS (SHOW DF, KDB, MCD, AND WD) 10. CLEVATIONS (SHOW DF, KDB, MCD, AND WD) 10. CLEVATIONS (SHOW DF, KDB, MCD, AND WD) 10. CLEVATIONS (SHOW DF, KDB, MCD, AND WD) 11. API NO. 11. API NO. 11. API NO. 11. API NO. 12. CLEVATIONS (SHOW DF, KDB, MCD, AN			Sec. 10:T-8-S, R-31-E, N.M.P.N
AT TOTAL DEPTH: Same 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 16. APPROPR. 17. APPROPR. 18. APPROPR. 18. Indeed, Check appropriate of the property of the p	AT SURFAC	E: 660' FWL and 660' FNL	12. COUNTY OR PARISH 13. STATE
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 15. ELEVATIONS (SHOW DF, KDB, AND WD) 4283 GR, 4293.5 KB REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE SHOOT OR ACIDIZE SHOOT OR ACIDIZE REPAIR WELL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other) Completion Information 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 10-10-83 Ran Schlumberger Cement Bond Log. Perforated: 3888, 3889, 3890, 3890.5, 3895, 3898, 3913, 3913.5, 3914, 3916, 3918, 3923, 3924.5, 3925.5, 3939.5, 3930.5, and 3931. Set 121 joints of 2-3/8", 4.6 S.T. & C., V-55, API Range 2 Tubing. Set Packer at 3787.01' Subsurface Safety Valve: Manu. and Type Set @ Ft. 18. I hereby certify that the foregoing is true and correct SIGNED May Title Suc. [NAL. DATE [1-17-8]]		OD: MITERIALE COMME	
REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES (other) Completion Information 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all merkers and zones pertinent to this work.)* 10-10-83 Ran Schlumberger Cement Bond Log. Perforated: 3888, 3889, 3890, 3890.5, 3895, 3898, 3913, 3913.5, 3914, 3916, 3918, 3923, 3924.5, 3925.5, 3939.5, 3930, 3930.5, and 3931. Set 121 joints of 2-3/8", 4.6 S.T. & C., V-55, API Range 2 Tubing. Set Packer at 3787.01' Subsurface Safety Valve: Manu. and Type Set @ Ft. 18. I hereby certify that the foregoing is true and correct SIGNED THE FIRE RECURBLY aspect for Federal or State office use)			14. API NO.
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING COMPLETE CHANGE ZONES ABANDON* (other) Completion Information 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 10-10-83 Ran Schlumberger Cement Bond Log. Perforated: 3888, 3889, 3890, 3890.5, 3895, 3898, 3913, 3913.5, 3914, 3916, 3918, 3923, 3924.5, 3925.5, 3939.5, 3930, 3930.5, and 3931. Set 121 joints of 2-3/8", 4.6 S.T. & C., V-55, API Range 2 Tubing. Set Packer at 3787.01' Subsurface Safety Valve: Manu. and Type Set @ Ft. 18. I hereby certify that the foregoing is true and correct SIGNED The Action of the Recurrence of the state of the use. ACTIFFIED THE RECURBLE spore for federal or State office use)			15. ELEVATIONS (SHOW DF, KDB, AND WD)
TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE SEPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON' (other) Completion Information 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 10-10-83 Ran Schlumberger Cement Bond Log. Perforated: 3888, 3889, 3890, 3890.5, 3895, 3898, 3913, 3913.5, 3914, 3916, 3918, 3923, 3924, 3924.5, 3925, 3939.5, 3939.5, 3930.5, and 3931. Set 121 joints of 2-3/8", 4.6 S.T. & C., V-55, API Range 2 Tubing. Set Packer at 3787.01' Subsurface Safety Valve: Manu. and Type Set @ Ft. 18. I hereby certify that the foregoing is true and correct SIGNED Label Completion of State office use) TITLE Sec. [NA. DATE 11-13-63]		ADDROVAL TO: CUREFOUGHT DEPORT OF	4283 GR, 4293.5 KB =
including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 10-10-83 Ran Schlumberger Cement Bond Log. Perforated: 3888, 3889, 3890, 3890.5, 3895, 3898, 3913, 3913.5, 3914, 3916, 3918, 3923, 3924, 3924.5, 3925, 3925.5, 3939.5, 3930, 3930.5, and 3931. Set 121 joints of 2-3/8", 4.6 S.T. & C., V-55, API Range 2 Tubing. Set Packer at 3787.01' Subsurface Safety Valve: Manu. and Type	FRACTURE TREAT		(NOTE: Report results of multiple completing or zero change on Form 9–330.)
Perforated: 3888, 3889, 3890, 3890.5, 3895, 3898, 3913, 3913.5, 3914, 3916, 3918, 3923, 3924, 3924.5, 3925, 3925.5, 3939.5, 3930, 3930.5, and 3931. Set 121 joints of 2-3/8", 4.6 S.T. & C., V-55, API Range 2 Tubing. Set Packer at 3787.01' Subsurface Safety Valve: Manu. and Type	including es	stimated date of starting any proposed work. If well is o	directionally drilled, give subsurface locations and
18. I hereby certify that the foregoing is true and correct SIGNED July Boydon TITLE Sec. True. DATE 11-17-83 ACCEPTED FUR RECURBING space for Foregal or State office use)	10-10-83	Perforated: 3888, 3889, 3890, 3913.5, 3914, 3916, 3918, 3923 3939.5, 3930, 3930.5, and 3931 Set 121 joints of 2-3/8", 4.6 Range 2 Tubing.	3890.5, 3895, 3898, 3913, 3, 3924, 3924.5, 3925, 39 25.5 ,
ACCEPTED FUN RECURMIS space for Federal or State office use) (ORIG. SGD.) DAVID R. GLASS APPROVED BY CONDITIONS OF APPROVAL (F. ANY 1983)	18. I hereby cer	tify that the foregoing is true and correct	
ORIG. SGD.) DAVID R. GLASS APPROVED BY CONDITIONS OF APPROVAL (F. ANY 1983		ACCEPTED FUN RECURMIS space for Federal or State of	ffice use)
	APPROVED BY	(ORIG. SGD.) DAVID R. GLASS APPROVAL R ANY 1983	DATE

DEC 16 1983
HOSES OFFICE