	STATE OF NEW MEXICO					
EN	AGY AND MINERALS DEPARTMENT OIL CONSERVATION DIVISION OISTRIBUTION PO. BOX 2008 SANTA FE, NEW MEXICO 37501		Form C-103 Revised 10-1-73			
	FILE     U3.0.3.     LAND OFFICE     OPERATOR			Se. Indicate Type State X 5, State Ott & Ge B1041	Fee	
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DATE ON TO DECREM OR PLUG BACK TO A DIFFERENT RESERVOIR. 1. 011. 012. 014.					7. Unit Agreement Name	
2. Name of Operator Enserch Exploration, Inc.					8. Farm or Lease Name STATE "13"	
3. Address of Operator 1230 River Bend Drive - Suite 136 - Dallas, Texas 75247					9. Well No. 1 10. Fleid and Pool, or Wildcat	
4. Location of Well UNIT LETTER 1980 FEET FROM THE South LINE AND 660' FEET FROM						
THE West LINE, SECTION 13 TOWNSHIP 12-S RANGE 31-E NMPM.						
J		15. Elevation (Show whether 4	DF, RT, GR, etc.) 420.9 GR	12. County Chaves		
16.	16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data   NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:					
TEM Pul	F DAM REMEDIAL WORK	PLUG A'17 ABANDON	REMEDIAL WORK		dures	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEZ RULE 1103.

Drilled an 8-3/4 inch hole to 12,010 feet. Ran logging suite consisting of DLL/MSFL/ Sonic/LDT/CNL/CAL/GR from 12,010 to 3600 feet. Ran Dipmeter from 12,010 to 10,500 feet. Re-entered and drilled to 12,060 feet and ran 5-1/2 inch casing to 12,060 feet consisting of 11.60#, N-80 & K-55 STC pipe. Production casing was cemented into place using a two stage cementing procedure. The first stage cement was composed of 255 sacks 50/50 Poz "H" + 5#/sk salt + 0.6% Halad-22A followed by 1000 sacks Class "H" + 4#/sk KCL + 0.4% Halad-22 + 0.5% CFR-2. Dropped bomb and shifted multi-stage tool open at 8216 feet, and circulated 4 hours. Cemented second stage with 705 sacks 50/50 Poz "H" + 6#/sk salt + 0.6% Halad-22A. Had good circulation throughout both stages and floats held okay. Set 5-1/2 inch casing slips with 150,000 lb and released rig on 3-10-84 at 11:00 A.M. Subsequent Sundry Notices will be handled by our Midland Production Department.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.					
		mcRegional Drilling Manager	DATE April 6, 1984		
an a	reepies				
	ORIGINAL SIGNED BY JERRY SEXTON		APR 1 0 1001		
APPROVED BY	DISTRICT 1 SUPERVISOR	TITLE			
	OF APPROVAL, IF ANYI				

r

