

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION  
P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
LG-1397	
7. Unit Agreement Name	
8. Farm or Lease Name	
Chaveroo State	
9. Well No.	
1	
10. Field and Pool, or Wildcat	
Chaveroo-San Andres	
12. County	
Chaves	

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator
Siete Oil and Gas Corporation
3. Address of Operator
Post Office Box 2523, Roswell, New Mexico 88201
4. Location of Well
UNIT LETTER <u>H</u> 1980 FEET FROM THE <u>North</u> LINE AND <u>660</u> FEET FROM THE <u>East</u> LINE, SECTION <u>4</u> TOWNSHIP <u>8S</u> RANGE <u>32E</u> NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUS AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <u>Set surface casing</u> <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUS AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

12/13/83 T.D. surface 1809' - at 8:45 A.M. - Ran 43 joints (1814') of 8 5/8", 24# casing and set at 1808' K.B. - cemented 550 sxs. Halliburton Lite, 1/4# flocl, 2% C.C. and 100 sxs. Class "C" with 2% C.C. - Cement circulated - Plug down at 7:00 P.M.

12/14/83 After waiting on cement for 18 hours, pressure up to 1000# for thirty (30) minutes - B.O.P. and casing held ok. - started drilling shoe at 1:00 P.M.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED C. J. Longo

TITLE Drilling Engineer

DATE December 15, 1983

ORIGINAL SIGNED BY EDDIE SEAY

APPROVED BY OIL & GAS INSPECTOR

TITLE

DEC 19 1983

DATE

CONDITIONS OF APPROVAL, IF ANY:

DEC 16 1983

HOBBY CHIEF