		Transfer	_	
Form 9–331 $\widehat{I}^{\pm \frac{1}{2}}$ Dec. 1973 UNITED STATES			Approved. et Bureau No. 42–R1424	
		5. LEASE		
DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY			NM-56244	
			6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
SUNDRY NO	TICES AND REPO	RTS ON WELLS	7. UNIT AGREEMENT N	AME
(Do not use this form for reservoir, Use Form 9-3:	or proposals to drill or to dee 31–C for such proposals.)	en or plug back to a will dent	8 FARM OR LEASE NAM	IE
1. oil gas well X we	s	NOV 2 1 1983	Curry & Thornto 9 WELL NO.	on-Federal #1
2. NAME OF OPER	RATOR	O. C. D.	1	1000
Siete Oil and Gas Corporat on ARTESIA, OFFICE 3. ADDRESS OF OPERATOR			1d FIELD OR WILDCAT NAME Siete-East San Andres	
	perator 523, Roswell, Nei	Mexico 88201	11. SEC., T., R., M., OR E	
4. LOCATION OF V	WELL (REPORT LOCATIO	N CLEARLY. See space 17	AREA	
below.)			Sec. 11: T-8-5	S. R-31-E N.M.P.M.
AT SURFACE: 2310 FSL 660 FWL AT TOP PROD. INTERVAL: Same			Chaves	
AT TOTAL DEPT			14. API NO.	·
		TE NATURE OF NOTICE,		. 22 (422 442)
REPORT, OR O	THER DATA		15. ELEVATIONS (SHOW 4337 GR	DF, KDB, AND WD)
REQUEST FOR APP	ROVAL TO: SUBS	SEQUENT REPORT OF:	<u> 4337 GR</u>	
TEST WATER SHUT FRACTURE TREAT	C-OFF			
SHOOT OR ACIDIZE				,
REPAIR WELL	461316		(NOTE: Report results of m change on Form 9-	ultiple completion or zone
PULL OR ALTER C MULTIPLE COMPLE	=			OFPI OFFI
CHANGE ZONES			a de la constante de la consta	
ABANDON* (other) Sur	∟ face Casing	Ш		No.
	•	0050471040 (01 - 11-	tII nestinent details and	give pertingny Alles
including actim	ated date of starting any	proposed work. If well is of markers and zones pertine	te all pertinent details, and directionally drilled, give subtract to this work.)*	OSL 6 N. A.
10-31-83	Spudded 12 1/4"	hole at 9:30 P.M.		NEW WEXICO
11-01-83	Drilling			
11-02-83	T.D. surface 1405' - 7:15 A.M Ran 35 joints of 8 5/8", 24# casing and set at 1405' K.B.M Cemented 500 sxs. Halliburton Lite, 1/4# flocel, 2% C.C. and 100 sxs. Class "C" with 2% C.C., Cement circulated - Plug down at 2:45 P.M.			
11-03-83	After W.O.C. for 18 hours, pressure up to 1000# for thirty (30) minutes - B.O.P held ok. Started drilling shoe at 1:00 P.M.			
Subsurface Safety \	Valve: Manu. and Type		Se	t @ Ft.
18. I hereby cortify	that the foregoing is true	and correct		
SIGNED	// //	TITLE President	DATE Novembe	r 8, 1983
ACCEPTED FOR RECORD'S space for Federal or State office use)				
APPROVED BY (ORIG. SGD.) DAVID R. GLASS DATE				
CONDITIONS OF APP	PROKID VF 1"7" 1983			