

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
Artesia, NM 88210

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	5. LEASE DESIGNATION AND SERIAL NO. NM 39643
2. NAME OF OPERATOR Wilson & Sons Energy, Inc.	6. IF INDIAN, ALLOTTEE OR TRIBE NAME NA
3. ADDRESS OF OPERATOR 600 N. Mareinfeld, Ste. 500, Midland, Texas 79701	7. UNIT AGREEMENT NAME NA
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' FSL & 660' FEL of Sec. 7	8. FARM OR LEASE NAME Carson Federal
14. PERMIT NO.	9. WELL NO. 1
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4186' K.B.	10. FIELD AND POOL, OR WILDCAT Wildcat - San Andres
	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 7-9S-31E
	12. COUNTY OR PARISH Chaves
	13. STATE N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
(Other) ☐

PULL OR ALTER CASING ☐
MULTIPLE COMPLETION ☐
ABANDON* ☒
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒
FRACTURE TREATMENT ☐
SHOOTING OR ACIDIZING ☐
(Other) ☐

REPAIRING WELL ☐
ALTERING CASING ☐
ABANDONMENTS ☒

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

83
The Carson Federal No. 1 well was spudded on 11/27/84. 8 5/8" OD, 24# casing was set at 1196' and cemented to surface. T.D. was 3900' and 4 1/2" OD, 10.5# casing was set at 3882' KB and cemented with 275 sks of cement. Top of cement is at 2880'. The San Andres was perforated at 3762-3767' 3742-3748' 3691-3694', 3686-3689' and 3676-3682'. The well was non-productive and plugged as per BLM District recommendations. Plugging procedure as follows: Set CIBP at 3656 and dumped 35' of cement on top. Set 100' cement plug at 3750-2850' (4 1/2" was cutt of @ 2800'). Set 100' cement plug at 1146-1246'. Set 50' cement plug at surface.

RECEIVED
FEB 28 10 08 AM '84
BUREAU OF LAND MGMT
ROSWELL DISTRICT

18. I hereby certify that the foregoing is true and correct

SIGNED Peter W. Chester TITLE Drilg./Prod. Manager DATE 2/23/84

(This space for Federal or State office use)

APPROVED BY PETER W. CHESTER TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

FEB 28 1986

BUREAU OF LAND MANAGEMENT See Instructions on Reverse Side
ROSWELL RESOURCE AREA