STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMI

He, or torics AttitleD		
DISTRIBUTION		
\$467.4 ME		
FILE		
U.S.G.S.		
LARD OFF -: F		
OPPGA		1

WELL X . Name of Operator

. Address of Operator

. I cration of hell

FULL OR ALTER CABING

HO, OF COPIES ACCLIVED	OIL CONSERVATION DIVISION
DISTRIBUTION	P. O. BOX 2088
34574 ME	SANTA FE, NEW MEXICO'87501
FILE	
U.\$.G.\$.	
LARO OFFICE	

GY AND MINERALS DEPARTMEN	ïΤ		
MO. OF COPIES ACCLIVED	OIL CONSERVA	TION DIVISION	
DISTRIBUTION	P. O. BOX	C 2088	For⊕ C-103 Revised 10-1-73
ARTA ME	SANTA FE, NEW	MEXICO:87501	Kevised 19-1-70
FileK	·		Sa. Indicate Type of Lease
J. S. G. S.			State Foe X
AND OFFICE			
DPPAA.CT			5. State Oil & Gas Leane No.
SUNDRY	NOTICES AND REPORTS ON OSALS TO DRILL ON TO DEEPEN OR PLUG BON FOR PERMIT - " (FORM C-101) FOR SUL	WELLS ACK TO A DIFFERENT RESERVOIR. H PROPOSALS.)	
			7. Unit Agreement Name
L X WELL	OTHER-		
e of Operator			8. Farm or Lease Name
Yates Petroleum Corpo	oration		Lightcap "YR"
	JIALION		9, Well No.
ess of Operator			2
207 South 4th St., An	rtesia, NM 88210		
ation of Well		•	10. Field and Pool, or Wildcut
D 9	990 FEET FROM THE North	LINE AND 990 FEET PRO	Wildcat SA
	31 TOWNSHIP 7		
	15. Elevation (Show whether	DF, RT, GR, etc.)	12. County
	4191' GR		Chaves
Check A	ppropriate Box To Indicate N	ature of Notice, Report or O	ther Data
NOTICE OF IN	TENTION TO:	SUBSEQUEN	IT REPORT OF:
·			
RM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING
<u> </u>	<u> </u>	COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT
MARILY AHAHDON	CHANGE PLANS	CASING TEST AND CEMENT JOB X	
OR ALTER CABING	CKANGE PLANS	Contra ten Man cement 3de V	

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1903.

Spudded 22" hole 9:05 PM 2-21-84. Set 34' of 16" conductor pipe. Resumed drilling with rotary tools 2:00 PM 2-24-84. Hole size 12-1/4". Ran 8-5/8" 24# K-55 casing set 337'. 1-Texas Pattern notched guide shoe set 337'. Insert float set 297'. Cemented w/225 sacks Class "C" 2% CaC12. Compressive strength of cement - 1250 psi in 14 hrs. PD 7:45 PM 2-24-84. Bumped plug to 1000 psi, released pressure and float held okay. Cement circulated 50 sacks. WOC. Drilled out 7:45 AM 2-25-84. WOC 12 hrs. Nippled up and tested to 1000# for 30 minutes, released pressure, float and casing held okay. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

8. I hereby certify that the information above is true and compl		
16Her Carrila & bollett	Production Supervisor	
ORIGINAL SIGNED BY JERRY SEXTON DISTRICT I SUPERVISOR	YITLE	•ATEMAR 5 1984

MAR 2 1984