

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐  
2. NAME OF OPERATOR  
Petroleum Exploration Company, Inc.  
3. ADDRESS OF OPERATOR  
Post Office Box 809, Roswell, NM 88201  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1980' FNL & 660' FEL  
AT TOP PROD. INTERVAL: Same  
AT TOTAL DEPTH: Same  
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>
(other) Surface Casing <input type="checkbox"/>	<input type="checkbox"/>

5. LEASE  
NM 067707  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
7. UNIT AGREEMENT NAME  
8. FARM OR LEASE NAME  
West Siete Federal  
9. WELL NO.  
#1  
10. FIELD OR WILDCAT NAME  
Siete - San Andres  
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 18  
T-8-S, R-31-E  
12. COUNTY OR PARISH  
Chaves  
13. STATE  
NM  
14. API NO.  
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
4187 GL, 4197 DF

(NOTE: Report results of multiple completion or zone change on Form 9-330)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent data, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*
- 3/24/84 Spudded 12½" Hole at 10:30 a.m.
- 3/25/84 Drilled to 1165'. Ran 1145' of 8-5/8", 24#, J-55 casing. Set at 1158'. Cemented with 350 sks. pace setter lite and 100 sks Class "C" with 2% CACL. Circulated 100 sks. Plugged down at 12:30 p.m. Waiting on cement.
- 3/26/84 Pressure tested blow out preventors to 1500# psi for 30 minutes. Held O.K. Started drilling out shoe 6:30 p.m.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Wesley Boylen TITLE Secretary/ Treas. DATE March 26, 1984

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL PETER W. CHESTER  
APR 9 1984

RECEIVED BY  
APR 12 1984  
O. C. D.  
ARTESIA, OFFICE

RECEIVED  
APR 17 1984  
O.C.D.  
HOBBS OFFICE