Form 3160-5 November 1983) Formerly 9-331)

UN ED STATES NISUBALIT CENTER IN DEPARTMEN OF THE INTERIOR (Other instruction.

Form approved. Budget Bureau No. 1004-0135 Expires August 31, 1985 5. LEASE DESIGNATION AND SERIAL NO.

-1 W17 1 100 F-14 1	٠.					_
BUREAU OF L	LAND	MANAGEMENT	Artesia,	${ m NM}$	88210	

NM 0256521

SUNDRY	NOTICES	AND	REPORTS	ON	WELLS
use this form fo	r proposals to	drill or to	deepen or plug	back to	a different reservoir.

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

(Do not use this form for Use "A	proposals to drill or to deepen or plug back to a different reservoir. PPLICATION FOR PERMIT—" for such proposals.)		
OIL GAS WELL OT	THEB	7. UNIT AGREEMENT NA	AMB
2. NAME OF OPERATOR		8. PARM OR LEASE NAI	NE .
Yates Drilling	Company	Burkitt Fede	eral
3. ADDRESS OF OPERATOR		9. WALL NO.	
207 South 4th S	t., Artesia, NM 88210	2	
4. LOCATION OF WELL (Report loc See also space 17 below.)	Undes. Queen 11. SBC., T., B., M., OR BLE. AND BURYRY OR AREA		
At surface			
1650 FNL			
	j ku sa sa sa	Unit E, Sec.	34-12S-31E
14. PERMIT No.	15. ELEVATIONS (Show whether DF, RT, GR, etc.)	12. COUNTY OR PARISE	13. STATE
	4222' GR	Chaves	NM
16. Ch.	ek Appropriate Boy To Indicate Nation of Nation Passas	- Osh D-s-	·

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

				•			
NOT	ICE OF INTE	INTION TO:		AUB	SSQUBNT REPORT	OF:	
TEST WATER SHUT-OFF		PULL OR ALTER CASING		WATER SHUT-OFF	X	REPAIRING WELL	
FRA TURE TREAT		MULTIPLE COMPLETE		FRACTURE TREATMENT		ALTERING CASING	
SHOOT OF ACIDIZE		ABANDON*		SHOOTING OR ACIDIZING		ABANDONMENT*	
REPAIR WELL	<u> </u>	CHANGE PLANS		(Other)			
(Other)				(NOTE: Report res Completion or Reco	ults of multiple supletion Report	completion on Well and Log form.)	

17 HIS RIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any peoposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and sones pertinent to this work.)

Spudded 12-1/4" hole 11:15 AM 5-5-84. Ran 9 joints of 8-5/8" 24# J-55 casing set 370'. 1-Texas Pattern netched guide shoe set 370'. Auto-fill insert float set 330'. Cemented w/250 sacks Class "C" 25% Poz, 1/4#/sack flocele. Tailed in w/125 sacks Class "C" 3%CaCl2. Compressive strength of cement - 1250 psi in 12 hours. PD 8:48 PM 5-5-84. Bumped plug to 1000 psi, released pressure and float held okay. Cement circulated 45 sacks. WOC. Drilled out 2:48 PM 5-6-84. WOC 18 hours. Nippled up and tested to 1000 psi for 30 minutes, OK. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

}			
I servely certify that the foregoing is true and correct			
SINE CARTE Problette	TITLE .	Production Supervisor	DATE 5-15-84
This space for Federal or Section Back Green ECORD			
CONDITIONS OF APPROVAL, IF ANY: MAY 17 1984	TITLE .		DATE
1 4			

MAY 21 1984
O. C. D.
ARTESIA, OFFICE

MAY 28 1984
HOURS OFFICE