Cormerly 9–331) DEPARTN	JNITED STATES IE OF THE INTER J OF LAND MANAGEMEN	IOR verse ade T Artesia, NM 88210	Expires Augus 55500 DESIGNATION NM 015807	No. 1004-0135	
(Do not use this form for propose	CES AND REPORTS (als to drill or to deepen or plug TION FOR PERMIT-" for such p	ON WELLS back to a different reservoir.	6. IF INDIAN, ALLOTTI	E OR TRIBE NAME	
I. OIL CAS WELL WELL OTHER	7. UNIT AGREEMENT NAME				
2. NAME OF OPERATOR			8. FARM OR LEASE NAME		
Yates Drilling Company			Garner Federal		
3. ADDEESS OF OPERATOR			9. WBLL NO.	9. WELL NO.	
207 South 4th St., Artesia, NM 88210			2	2	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements."			10. FIELD AND POOL,	10. PIELD AND POOL, OR WILDCAT	
See also space 17 below.) At surface	Undes. Caprock Queen				
2310 FSL & 2310 FEL, Sec. 34-12S-31E			11. SBC., T., R., M., OR BLK. AND SURVEY OR AREA		
				<u>. 34-T12S-R</u> 31E	
14. PERMIT NO.	15. ELEVATIONS (Show whether D	F, RT, GR, etc.)	12. COUNTY OR PARIS	H 13. STATE	
	4430' GR		Chaves	NM	
16. Check Ap	propriate Box To Indicate P	Nature of Notice, Report, or	Other Data		
NOTICE OF INTENTION TO:		QUENT REPORT OF :	IBNT REPORT OF :		
	CLL OR ALTER CASING	-	X REPAIRING		
	ULTIFLE COMPLETE	FRACTURE TREATMENT	ALTERING (

17 DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and gones pertinent to this work.)*

CHANGE PLAN:

REPAIR WELL

(Other)

(Other) Surface & Production Casing

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

X

Spudded 12-1/4" hole 6:15 PM 4-29-84. Ran 10 joints of 8-5/8" 24# J-55 casing set 410'. Cemented w/250 sacks 75/25 Poz, 3% CaCl2 and 1/4# flocele/sack. Compressive strength of cement - 1275 psi in 12 hours. PD 7:00 AM 4-30-84. Bumped plug to 1000 psi, released pressure and float held okay. Cement circulated 50 sacks. WOC. Drilled out 1:30 PM 5-1-84. WOC 18 hours. Nippled up and tested to 1000# for 30 minutes, OK. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

TD 3100'. Ran 78 joints of 5-1/2" 14# & 15.5# J-55 ST&C casing as follows: 76 joints of 5-1/2" 14# J-55 ST&C and 2 joints of 5-1/2" 15.5# J-55 casing set at 3098'. 1-float shoe set 3098'. Cemented w/350 sacks 75% "C", 25% LitePoz, 5#/sack salt, 1/4#/sack flocele, 1% CaCl2. Tailed in w/200 sacks Class "C" 1% CaCl2. Compressive strength of cement - 1000 psi in 12 hours. PD 1:30 PM 5-4-85. Bumped plug to 1000# for 30 minutes, released pressure, float and casing held okay. WOC 18 hours.

since the state of	TITLE Production Supervisor	DATE 5-15-84
APPROVED BY PETER W PETER CONDITIONS OF APPROVAL, IF ANY: MAY 17 1984		DATE
*Se	e Instructions on Reverse Side	

The 18 of S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any faise, Sictitious or fraudulent statements or representations as to any matter within its jurisdiction.

MAY 28 1984 HOESS UFFICE

¥

O. C. D. 4861 I S YAM RECEIVED BY

۴.