

Form 9-331  
Dec 1973

RECEIVED

AUG 27 1984

UNITED STATES

DEPARTMENT OF THE INTERIOR

GEOLOGICAL SURVEY

ARTESIA, NM

NM OIL CONS. COMMISSION

Drawer DD

Artesia, NM 88210

Form Approved.

Budget Bureau No. 42-R1424

### SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐  
well well other

2. NAME OF OPERATOR  
Petroleum Exploration Co., Inc.

3. ADDRESS OF OPERATOR  
P.O. Box 809, Roswell, NM 88201

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 2310' FSL & 990' FEL  
AT TOP PROD. INTERVAL: Same  
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) 4 1/2" Casing

5. LEASE  
NM 067707

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Siete-Federal

9. WELL NO.  
#5

10. FIELD OR WILDCAT NAME  
Siete-San Andres

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 17  
T-8-S, R-31-E

12. COUNTY OR PARISH  
Chaves

13. STATE  
NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
4202' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

8-14-84 TD 3860'. Ran compensated Neutron Formation Density with Gamma Ray & Dual Lateral Micro SFL Logs.

8-15-84 Ran 93 jts (3803') of 4 1/2" 9.5#, J-55 API Casing. Set at 3817'. Cemented with 150 sxs of lite "C" & 200 sxs. of class "C" cement with 2% KCL, .5% CF-1 fluid loss & 2% anti-foaming agent. Waiting on Completion.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

*Wesley Boggs*

TITLE

*Sec/Tres*

DATE

*8-17-84*

(This space for Federal or State office use)

ACCEPTED FOR RECORD

APPROVED BY

CONDITIONS OF APPROVAL IF ANY, CHESTER

TITLE

DATE

AUG 24 1984

\*See Instructions on Reverse Side

