

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐

2. NAME OF OPERATOR
Petroleum Exploration Co., Inc.

3. ADDRESS OF OPERATOR
Post Office Box 809, Roswell, NM 88201

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 2310' FSL & 990' FEL
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	<input type="checkbox"/>		<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>		<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>		<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>		<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>		<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>		<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>		<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>		<input type="checkbox"/>
(other) Surface Casing			

5. LEASE
NM 067707

6. IF INDIAN, ALLOTTEE OR TRIBE NAME
-

7. UNIT AGREEMENT NAME
-

8. FARM OR LEASE NAME
Siete-Federal

9. WELL NO.
#5

10. FIELD OR WILDCAT NAME
Siete-San Andres

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 17
T-8-S, R-31-E

12. COUNTY OR PARISH
Chaves

13. STATE
NM

14. API NO.
-

15. ELEVATIONS (SHOW DF, KDB, AND WD)
4202' GL, 4212' KB

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8-6-84 Spudded 12 1/4" hole @ 5:00 p.m.

8-7-84 Drilled to 1120'. Ran 1101' of 8 5/8" 24#, K-55 Casing. Set @ 1114'. Cemented with 350 sks Lite "C" & 100 sks class "C" with 2% CaCl₂. Circulated 70 sks. Plugged down 2 4:00 a.m. W.O.C. for 18 hours.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Wesley Boyden TITLE Sec./Tres. DATE 8-8-84

ACCEPTED FOR RECORD (This space for Federal or State office use)

APPROVED BY PETER W. CHESTER TITLE _____ DATE _____
CONDITIONS OF APPROVAL IF ANY:

AUG 13 1984

RECEIVED BY
AUG 15 1984
O. C. D.
ARTESIA, OFFICE

RECEIVED
AUG 16 1984
O.C.D.
HOEBS OFFICE