

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO. <u>30-005-20975</u>
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No. —
7. Lease Name or Unit Agreement Name <u>Doyal</u>
8. Well No. <u>1</u>
9. Pool name or Wildcat <u>SE Chaves On Gas Area Assoc.</u>
10. Elevation (Show whether DF, RKB, RT, GR, etc.) <u>4428' GL</u>

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:  
OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. Name of Operator  
Yates Drilling Company

3. Address of Operator  
105 South 4th Street, Artesia, NM 88210

4. Well Location  
Unit Letter A : 660 Feet From The North Line and 990 Feet From The East Line

Section 34 Township 12S Range 31E NMPM Chaves County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)  
4428' GL

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

REMEDIAL WORK ☐ ALTERING CASING ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

PULL OR ALTER CASING ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Convert to Water Injection Well ☒

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

We propose to convert the subject well to water injection under the provisions of order R-9075 and R-9075-B.

1. Flush perforations w/1000 gals. 7½% HCL.
2. Set plastic lined tbg. @ approximately 2932' w/ injection packer.
3. Fill annulus w/ inert fluid.
4. Commence injection.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tobin L. Rhodes TITLE Engineer DATE 8-1-90

TYPE OR PRINT NAME Tobin L. Rhodes TELEPHONE NO. 748-1471

(This space for State Use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE AUG - 6 1990

CONDITIONS OF APPROVAL, IF ANY: