

REORDER NO.

DEPTH 10695 FT.

INITIAL SHUT-IN

INITIAL FLOW TIME: T 15 MIN.

DT(MIN)	LOG((T+DT)/DT)	PRESSURE(PSIG)	DP(PSIG)
0		958.0	0.0
2	.979	983.0	25.0
4	.677	1051.0	93.0
6	.944	1241.0	283.0
8	.459	1595.0	637.0
10	.398	2092.0	1134.0
12	.352	2644.0	1686.0
14	.316	2816.0	1858.0
24	.211	2766.0	1808.0
36	.151	2753.0	1795.0
48	.118	2749.0	1791.0
60	.097	2751.0	1793.0
72	.082	2751.0	1793.0
84	.071	2751.0	1793.0
96	.063	2751.0	1793.0
108	.056	2751.0	1793.0
120	.051	2751.0	1793.0

EXTRAPOLATED PRESSURE: INDETERMINATE - ERRATIC BUILD-UP CURVE

FINAL SHUT-IN

TOTAL FLOW TIME: T = 105 MIN.

DT(MIN)	LOG((T+DT)/DT)	PRESSURE(PSIG)	DP(PSIG)
0		1310.0	0.0
2	1.728	1852.0	42.0
4	1.435	1983.0	173.0
6	1.267	2481.0	671.0
8	1.150	2548.0	738.0
10	1.061	2565.0	755.0
12	.989	2582.0	772.0
18	.835	2615.0	805.0
36	.593	2661.0	851.0
54	.469	2678.0	868.0
72	.391	2690.0	880.0
90	.336	2699.0	889.0
108	.295	2705.0	895.0
126	.263	2709.0	899.0
144	.238	2711.0	901.0
162	.217	2711.0	901.0

EXTRAPOLATED PRESSURE: 2700.6 PSI

SLOPE: 140.1 PSI/LOG CYCLE

POINTS USED: 8