

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-71

5a. Indicate Type of Lease
State ☒ Fee ☐
5. State Oil & Gas Lease No.
LH-1320

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER- ☐

Name of Operator SPENCE ENERGY COMPANY	7. Unit Agreement Name
Address of Operator 31 Two Energy Square, 4849 Greenville Ave., Dallas, Texas 75206	8. Farm or Lease Name State "22"
Location of Well UNIT LETTER C 660 FEET FROM THE North LINE AND 1980 FEET FROM THE West LINE, SECTION 22 TOWNSHIP 8 South RANGE 33 East NMPM.	9. Well No. 2
	10. Field and Pool, or Wildcat Chaveroo
15. Elevation (Show whether DF, RT, CR, etc.) 4367.8' G. L.	12. County Chaves

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

FORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

2/24/85 Spud @ 6:15 P.M., 12½" hole @ 416', ran 10 jts. 24# 8 5/8" csg. Cemented w/285 sxs of Class "C" - 2% Calc Chl. Plug Down @ 12:15 A.M., Circulated 70 sxs to Pits.

3/3/85 Drld to TD of 4442'. Prep to log. Marker @ 4130'.

3/7/85 Ran Wellex Dual Laterolog & compensated Density Neutron Gamma Ray Laterologs to TD of 4442'. Ran 105 jts of 5½" 15.5# J-55 prod csg. Set out on bottom @ 4442'. Ran float shoe with latch down plug & baffle. Ran 10 bbls. of 2% Kel water & 500 bbls. mud flush, 10 bbls Kel water ahead of cmt. Cemented with 185 sxs. 50-50 Poz Class "C" with 2% gel. Plug Dwn @ 5:00 A.M. Rig released @ 6:00 A.M. Waiting on Cement.

Hereby certify that the information above is true and complete to the best of my knowledge and belief.

by Robert C. Spence TITLE Production Clerk DATE 3/11/85
Robert C. Spence
ORIGINAL SIGNED BY HARRY SEXTON
DISTRICT SUPERVISOR
MAR 18 1985

RECEIVED

MAR 18 1985

A.C.D.
HONORARY OFFICE