

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other

2. NAME OF OPERATOR
Yates Drilling Company

3. ADDRESS OF OPERATOR
207 South 4th Street, Artesia, N.M. 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 660' FSL & 990' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other)

☒
☐
☐
☐
☐
☐
☐
☐

5. LEASE

NM-15896

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

DeLuna Federal

9. WELL NO.

#4

10. FIELD OR WILDCAT NAME

S.E. Chaves Queen Gas Area Assoc.

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 22-T12S-R31E

12. COUNTY OR PARISH 13. STATE

Chaves

N.M.

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

4433' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 12 1/4" hole 9:30 P.M., 2-22-85.

Ran 11 joints 8 5/8" 24# J-55 casing set at 439'. 1-Regular Notched Pattern guide shoe set at 439'. Insert flapper float set 425'. Cemented with 250 sacks Class "C" 3% CaCl₂ and 1/4#/sack floseal in 1st 125 sacks. Compressive strength of cement 1275 psi in 12 hours. PD 2:02 P.M., 2-23-85. Bumped plug to 1000 psi, released pressure and float held okay. Cement did not circulate. Redi-mixed 7 yards to fill outside 8 5/8" to surface. WOC. Reduced hole to 7 7/8". Drilled plug and resumed drilling.

Subsurface Safety Valve: Manu. and Type

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED *Peter W. Chester*

TITLE Production Clerk

DATE 2-28-85

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

(This space is for record office use.)

PETER W. CHESTER
TITLE

DATE

MAR 8 1985

BUREAU OF LAND MANAGEMENT
ROSWELL RESOURCE AREA



RECEIVED
MAR 12 1985
O.C.D.
HONORABLE OFFICE