

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radioactivity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

Rustler	2030	T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Anhy		T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
T. Salt		T. Atoka	T. Pictured Cliffs	T. Penn. "D"
B. Salt	2560	T. Miss	T. Cliff House	T. Leadville
T. Yates		T. Devonian	T. Menefee	T. Madison
T. 7 Rivers		T. Silurian	T. Point Lookout	T. Elbert
T. Queen		T. Montoya	T. Mancos	T. McCracken
T. Grayburg	3760	T. Simpson	T. Gallup	T. Ignacio Qtzte
T. San Andres	5104	T. McKee	Base Greenhorn	T. Granite
T. Glorieta		T. Ellenburger	T. Dakota	
T. Paddock		T. Gr. Wash	T. Morrison	
T. Blinberry	6638	T. Granite	T. Todilto	
T. Tubb		T. Delaware Sand	T. Entrada	
T. Drinkard	7476	T. Bone Springs	T. Wingate	
T. Abo		T. Bough B	T. Chinle	
T. Wolfcamp Lm	8582	T. Bough C	T. Permian	
T. Penn.			T. Penn. "A"	
T. Cisco (Bough C)				

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....	No. 4, from.....to.....
No. 2, from.....to.....	No. 5, from.....to.....
No. 3, from.....to.....	No. 6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.	
No. 2, from.....to.....feet.	
No. 3, from.....to.....feet.	
No. 4, from.....to.....feet.	

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	385	385	Surface, Redbeds, Rock				
385	826	441	Redbeds, Anhydrite				
826	3880	3054	Redbeds, Anhy, Salt, Dolo.				
3880	4446	566	Anhydrite, Dolomite				
4446	4644	198	Dolomite, Shale				
4644	4980	336	Lime				
4980	5280	300	Lime, Dolomite				
5280	5400	120	Lime, Sand				
5400	6000	600	Dolo, Sd. Shale, Lime, Shale				
6000	6200	200	Lime, Anhy, Dolo, Shale				
6200	6752	552	Anhy, Dolo, Lm, Shale, Sd				
6752	7296	544	Dolo, Anhy, Shale, Sand				
7296	7400	104	Dolo, Anhy, Lime, Sand				
7400	7500	100	Dolo, Anhydrite				
7500	8100	600	Shale				
8100	8550	450	Dolo, Shale				

RECEIVED

JUN -6 1985

G.C.D.
HOBBS OFFICE