

STATE OF NEW MEXICO.
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

RECEIVED BY
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501
APR - 5 1985
O. C. D.
ARTESIA, OFFICE

5a. Indicate Type of Lease	
State ☒	Fee ☐
5. State Oil & Gas Lease No. LG 2753	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO OPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. ☒ OIL WELL ☐ GAS WELL ☐ OTHER-		7. Unit Agreement Name
2. Name of Operator Yates Petroleum Corporation		8. Farm or Lease Name Brahman "ACC" State
3. Address of Operator 207 South 4th St., Artesia, NM 88210		9. Well No. 1
4. Location of Well UNIT LETTER <u>B</u> <u>990</u> FEET FROM THE <u>North</u> LINE AND <u>2310</u> FEET FROM THE <u>East</u> LINE, SECTION <u>16</u> TOWNSHIP <u>8S</u> RANGE <u>31E</u> NMPM.		10. Field and Pool, or Wildcat Siete SA
15. Elevation (Show whether DF, RT, GR, etc.) 4242' GR		11. County Chaves

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☒	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☒	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 12-1/4" hole at 10:00 PM 3-31-85. Ran 33 joints 8-5/8" 24# J-55 ST&C casing set 1343'. 1-guide shoe set 1343'. Insert float set 1301'. Cemented w/400 sx Pacsetter Lite, 1/4#/sack celloseal plus 2% CaCl2. Compressive strength of cement - 1250 psi in 12 hrs. PD 11:15 PM 4-1-85. Bumped plug to 1000 psi, released pressure and float held okay. Drilled out 5:30 PM 4-2-85. WOC 18 hrs and 15 minutes. NU and tested to 1000 psi for 30 minutes, OK. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Jerry Sexton TITLE Production Supervisor DATE 4-3-85
ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT 1 SUPERVISOR
DATE APR 15 1985
OF APPROVAL, IF ANY:

RECEIVED

APR 15 1985

O.C.D.
HOBBS OFFICE