N. M. OIL CORS. COMMISTA P. O. BOX 1980 HOBBS, NEW MEXICO 69240

Form 9-331 Dec. 1973	POLING, IXETE HIMPING		Form Approved. Budget Bureau No. 42-R1424		
	UNITED STATES	Γ	5. LEASE		
	DEPARTMENT OF THE INTERIOR		NM 067707		
GEOLOGICAL SURVEY			6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
	RY NOTICES AND REPORTS ON WELL is form for preposals to drill or to deepen or plug back to a diff- form 9-331-C for such proposals.)		7. UNIT AGREEMEN	T NAME	
reservoir, Use I	Form 9-331-C for such proposals.)		8. FARM OR LEASE	NAME	
1. oil	gas Other	-	Siete-Federa	<u>a1</u>	
	OF OPERATOR		9. WELL NO. #6		
Petroleum Exploration Company, Inc.			10. FIELD OR WILDCAT NAME		
3. ADDRESS OF OPERATOR			Siete-San Andres 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 17		
Post Office Box 809					
	ON OF WELL (REPORT LOCATION CLEARLY, See spec	æ 17	AREA Sec. 1		
below.) AT SURI	FACE: 2310' FSL & 1980' FWL	ŀ	12. COUNTY OR PAR		
	PROD. INTERVAL: Same	Ì	Chaves	NM	
AT TOTA	AL DEPTH: Same		14. API NO.		
	APPROPRIATE BOX TO INDICATE NATURE OF NOT , OR OTHER DATA	TICE,		· · · · · · · · · · · · · · · · · · ·	
		1		HOW DF, KDB, AND WD) 203 KB	
•	OR APPROVAL TO: SUBSEQUENT REPORT OF	F: "			
FRACTURE 1				•	
SHOOT OR ACIDIZE			(NOTE: Report results of multiple completion or zone change on Form 9–330.)		
CHANGE ZO	ONES				
ABANDON* (other)	LI LI				
			· · · · · · · · · · · · · · · · · · ·		
includin	BE PROPOSED OR COMPLETED OPERATIONS (Clearling estimated data of starting any proposed work. If we ad and true vertical depths for all markers and zones po	ell is di	rectionally drilled, give	and give pertinent dates, subsurface locations and	
5-11 -8 5	Ran cement Bond, Collar Locator and	d Gam	ma Ray Correlat	tion Logs.	
	Perforated 3674, 3675, 3676, 3681,	, 368	9, 3690, 3691,	3692, 3694,	
	3695, 3696, 3700, 3704, 3705, 3706, (19 Shots total). Ran in hole with	, 3/⊥ h 116	2, 3/13, 3/14 a its. (3745!) a	and 3/13.	
	4.7#, J-55 tubing. Set at 3752'.	11 110	Jes. (3/43) .	or 2 3/3 ,	
	(0,7 m, 0 33 0022 mg = 0 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2				
5 - 12 - 85	Acidized with 6000 gals. 20% HCL a	acid.			
Súbsurface :	Safety Valve: Manu. and Type			Set @ Ft.	
. •	certify that the foregoing is true and correct	_		•	
SIGNED WS	esly Bradan TITLE SEC 17	nes	DATE	S-85	
	ACCEPTED FOR RECORD CO. S.				
	PETER W. CHESTER				
APPROVED BY	OF APPROVAL, IF ANY:		DATE		
	MAY 2 8 1985				
	BUREAU OF LAND MANAGEMENT Instructions on Re		lda.		
	ROSWELL RESOURCE AREA	-v-: >C 3			