

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐
2. NAME OF OPERATOR
Petroleum Exploration Company, Inc.
3. ADDRESS OF OPERATOR
P.O. Box 809, Roswell, NM 88201
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 2310' FSL & 1980' FWL
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>
(other) Long String Casing Notice		

5. LEASE
NM 067707
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Siete-Federal
9. WELL NO.
#6
10. FIELD OR WILDCAT NAME
Siete San Andres
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 17
T8S, R31E
12. COUNTY OR PARISH
Chaves
13. STATE
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
4193 GL, 4203 KB

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

5-7-85 T.D. 3830'

5-8-85 Ran Compensated Neutron Denisity with Gamma Ray, Dual Lateral log, Micro SFL, and Bore Hole Sonic Logs. Ran 94 jts. (3809') of 4½", 10.5#, J-55 Casing. Set at 3820'. Cemented with 500 gal. of mud flush, 150 sx. of Halliburton Lite "C", and 200 sx. self expansion "H" cement with 10% calseal, .3% Halaad #4, .2% LFR-3 and 5# salt. Displaced with 2% KCL water. Plug down at 4:30 a.m. 5-9-85.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Wesley Bozdan TITLE Sec / Tres DATE 5/9/85

ACCEPTED FOR RECORD (This space for Federal or State office use)
PETER W. CHESTER
APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:
MAY 20 1985
BUREAU OF LAND MANAGEMENT
ROSWELL RESOURCE AREA
*See Instructions on Reverse Side

RECEIVED

MAY 22 1985

C.S.D.
HOSES OFFICE