

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

| | |
|------------------------|--|
| NO. OF COPIES RECEIVED | |
| DISTRIBUTION | |
| SANTA FE | |
| FILE | |
| U.S.G.S. | |
| LAND OFFICE | |
| OPERATION | |

5a. Indicate Type of Lease
State ☒ Fee ☐
5. State Oil & Gas Lease No.
LG 2754

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO OPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT - (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

1. Name of Operator
Yates Petroleum Corporation
2. Address of Operator
207 South 4th St., Artesia, NM 88210
3. Location of Well

7. Unit Agreement Name
8. Farm or Lease Name
Hereford ACB State
9. Well No.
1

UNIT LETTER H 1980 FEET FROM THE North LINE AND 660 FEET FROM
THE East LINE, SECTION 16 TOWNSHIP 8S RANGE 32E NMPM.

10. Field and Pool, or Wildcat
Wildcat

11. Elevation (Show whether DF, RT, GR, etc.)
4394' GR

12. County
Chaves

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☐
OTHER Perforate, Treat, Test ☒

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

10-26-85. Spot 35 sx cement plug at 8640-8320', in 5½" casing, tagged plug at 8480'. Set 20 sx plug at 6500-6300' in 5½" casing, tagged plug at 6289'.
10-27-85. Shot squeeze holes at 5570'. Ran cement retainer to 5500'. Cement squeezed w/30 sx Class C, .3% Halad-4 and 2% CaCl2. Perforated 4650' w/4 squeeze holes. Spot 250 g. mud flush. Cemented w/200 sx Class C w/.4% Halad-4 + 2% CaCl2.
11-4-85. Perforated 4365-4410' w/12 .50" holes as follows: 4365, 66, 67, 69, 71, 81, 83, 85, 86, 88, 4409½, 10½'. Treated perms w/1000 gals 15% NEFE acid and 10 ball sealers.
11-8-85. Set CIBP at 4350' w/35' cement on top. Shot 4 squeeze holes at 4280'. Cemented w/200 sx Class C. Retainer set at 4250'.
11-21-85. Perforated 4184-92' w/10 .40" holes. Treated perms 4184-92' w/1000 gals 15% NEFE acid.
11-23-85. Set cement retainer at 4178' w/wireline. Squeezed w/150 sx Class C + 2% CaCl2.
11-26-85. Perforated 4132-61' w/10 .50" holes. Treated perms 4132-61' w/1500 gals 15% NEFE acid + 10 ball sealers. Swabbed well to recover load.
12-6-85. Had small show of gas, skim of oil

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Jerry Sexton TITLE Production Supervisor

DATE 12-16-85

ORIGINAL SIGNED BY JERRY SEXTON

APPROVED BY DISTRICT 1 SUPERVISOR

TITLE

DATE DEC 20 1985

CONDITIONS OF APPROVAL, IF ANY: