

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
LG 2754	
7. Unit Agreement Name	
8. Farm or Lease Name	
Hereford "ACB" State	
9. Well No.	
1	
10. Field and Pool, or Wildcat	
Wildcat	
11. County	
Chaves	

SUNDARY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO OPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Name of Operator		2. Unit Agreement Name	
Yates Petroleum Corporation			
3. Address of Operator		8. Farm or Lease Name	
207 South 4th St., Artesia, NM 88210		Hereford "ACB" State	
4. Location of Well		9. Well No.	
UNIT LETTER <u>H</u> , <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>660</u> FEET FROM		1	
THE <u>East</u> LINE, SECTION <u>16</u> TOWNSHIP <u>8S</u> RANGE <u>32E</u> NMPM.		10. Field and Pool, or Wildcat	
		Wildcat	
15. Elevation (Show whether DF, RT, GR, etc.)		11. County	
4394' GR		Chaves	

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 17-1/2" hole at 6:30 AM 4-27-85. Ran 9 jts 13-3/8" 54.5# J-55 ST&C casing set 352'. 1-guide shoe set 352'. Insert float set 312'. Cemented w/370 sx Class "C" w/2% CaCl2. Compressive strength of cement - 1250 psi in 12 hrs. PD 9:00 AM 4-28-85. Bumped plug to 1000 psi, released pressure, held okay. Cement circulated 32 sacks. WOC. Drilled out 5:45 AM 4-29-85. WOC 20 hrs and 45 mins. NU and tested to 1000 psi for 30 minutes, OK. Reduced hole to 12-1/4". Drilled plug and resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE <u>Eddie Seay</u>	TITLE <u>Production Supervisor</u>	DATE <u>4-29-85</u>
APPROVED BY <u>ORIGINAL SIGNED BY EDDIE SEAY</u>	TITLE <u>OIL & GAS INSPECTOR</u>	DATE <u>MAY 6 1985</u>

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

MAY 6 1985

O.C.D.
HOBBS OFFICE