

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quadruplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico			Northwestern New Mexico		
T. Rustler	2008	T. Canyon	T. Ojo Alamo	T. Penn. "B"	
T. Anhy		T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"	
T. Salt		T. Atoka	T. Pictured Cliffs	T. Penn. "D"	
B. Salt	2532	T. Miss	T. Cliff House	T. Leadville	
T. Yates		T. Devonian	T. Menefee	T. Madison	
T. 7 Rivers		T. Silurian	T. Point Lookout	T. Elbert	
T. Queen		T. Montoya	T. Mancos	T. McCracken	
T. Grayburg		T. Simpson	T. Gallup	T. Ignacio Qtzte	
T. San Andres	3734	T. McKee	Base Greenhorn	T. Granite	
T. Glorieta	5090	T. Ellenburger	T. Dakota		
T. Paddock		T. Gr. Wash	T. Morrison		
T. Blinberry	6634	T. Granite	T. Todilto		
T. Tubb		T. Delaware Sand	T. Entrada		
T. Drinkard	7494	T. Bone Springs	T. Wingate		
T. Abo		T. Bough B	T. Chinle		
T. Wolfcamp Lime	8602	T. Bough C	T. Permian		
T. Penn.			T. Penn. "A"		
T. Cisco (Bough C)					

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....
 No. 2, from.....to.....
 No. 3, from.....to.....
 No. 4, from.....to.....
 No. 5, from.....to.....
 No. 6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....
 No. 4, from.....to.....feet.....

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	360	360	Surface, Redbeds				
360	2504	2144	Redbeds, Anhydrite				
2504	3380	876	Salt, Anhydrite				
3380	4514	1134	Dolomite, Anhydrite				
4514	5006	492	Dolomite, Anhydrite				
5006	5310	304	Anhy, Dolo, Lime, Sand				
5310	5486	176	Anhy, Sand, Shale, Lime				
5486	6050	564	Anhy, Shale, Sand, Dolo				
6050	6530	480	Anhy, Dolo, Sand, Sh. Lime				
6530	7540	1010	Anhy, Dolo, Shale, Sand				
7540	8040	500	Shale				
8040	8620	580	Shale, Dolomite				
8620	9060	440	Lime, Dolomite				
9060	9146	86	Lime, Chert, Shale				
9146	9439	293	Lime, Shale				

RECEIVED
FEB - 4 1986
O.C.D.
HOBBS OFFICE