

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
E-8250

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

Name of Operator
Yates Petroleum Corporation
Address of Operator
207 S. 4th St., Artesia, NM 88210

Location of Well
UNIT LETTER I 1980 FEET FROM THE South LINE AND 660 FEET FROM
THE East LINE, SECTION 27 TOWNSHIP 8S RANGE 33E NMPM.

7. Unit Agreement Name

8. Farm or Lease Name

Enstar ACW State

9. Well No.

1

10. Field and Pool, or wildcat
Tobac Penn

11. Elevation (Show whether DF, RT, GR, etc.)

4374.5' GR 4356

12. County

Chaves

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☒
CASING TEST AND CEMENT JOBS ☒
OTHER ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 17-1/2" hole at 11:00 PM 9-16-85. Ran 9 joints 13-3/8" 54.5# J-55 ST&C casing set 360'. 1-Texas Pattern notched guide shoe set 360'. Insert float set 319'. Cemented w/300 sxs Class "C" + 1/4#/sx Celloseal + 2% CaCl2. Compressive strength of cement - 1250 psi in 12 hrs. PD 11:45 AM 9-17-85. Bumped plug to 1000 psi, released pressure, float held okay. Cement circulated 20 sx to pit. WOC. Drilled out 12:45 AM 9-18-85. WOC 25 hrs. NU and tested to 1000 psi for 30 minutes, OK. Reduced hole to 11". Drilled plug and resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT 1 SUPERVISOR

TITLE Production Supervisor

DATE 9-19-85

SEP 23 1985

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED
SEP 23 1985
O.C.D.
HOBB'S OFFICE