

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☐ other ☐ dry hole
2. NAME OF OPERATOR
Maralo, Inc.
3. ADDRESS OF OPERATOR
P. O. Box 832, Midland, Texas 79701-0832
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FNL and 660' FEL of Section
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH: 1980' FNL and 660' FEL of Section

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF ☐ ☐
FRACTURE TREAT ☐ ☐
SHOOT OR ACIDIZE ☐ ☐
REPAIR WELL ☐ ☐
PULL OR ALTER CASING ☐ ☐
MULTIPLE COMPLETE ☐ ☐
CHANGE ZONES ☐ ☐
ABANDON* ☐ ☒
(other) Spud and casing ☐ ☒

5. LEASE
NM-40657
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Maralo Federal #
9. WELL NO.
1
10. FIELD OR WILDCAT NAME
Wildcat
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 4, T.9 S., R.31 E.
12. COUNTY OR PARISH
Chaves
13. STATE
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
4260.4 GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 7-31-85 @ 9:15 P.M.

8-2-85 Ran 11 jts. 13 3/8"; 61# & 54.5# ST&C casing. Set @ 424'. Cemented with 400 sacks Class "C" w/2% CaCl & 1/4#/sx cello seal. Cement circulated. 12 1/2" hole. Tested to 1200 psi - okay.

8-11-85 P&A'd as follows:

25 sack cement plug 3124 - 3024'
25 sack cement plug 1928 - 1828'
50 sack cement plug 474 - 374'.
25 sacks cement plug 60 - Surface.

Cut off wellhead and installed dry hole marker

Note: Notified Bureau of Land Management prior to plugging - no witness.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Brenda Callman TITLE _____ Agent SEP 13 1985 Sept. 12, 1985

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

Approved as to plugging of the well bore
Liability under bond is retained until
surface restoration is completed.

*See Instructions on Reverse Side

APPROVED
PETER W. CHESTER
FEB 11 1987
BUREAU OF LAND MANAGEMENT
ROSWELL RESOURCE AREA

RECEIVED
FEB 25 1987
OCD
HOBBS OFFICE