

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐

2. NAME OF OPERATOR
Robert N. Enfield

3. ADDRESS OF OPERATOR
P.O. Box 2431, Santa Fe, NM 87501

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980' FSL & 990' FWL of Sec. 3.

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

☐
☐
☐
☐
☐
☐
☐
☐

(other) SET INTERMEDIATE CASING X

5. LEASE
NM 15895

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Carson Federal

9. WELL NO.
1

10. FIELD OR WILDCAT NAME
Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 3, T9S, R31E

12. COUNTY OR PARISH
Chaves

13. STATE
NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
4277.5 GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

A 12-1/4" hole was drilled from 487' to 2087' and 11" hole from 2087' to 3500'
8/22/85 - 8-5/8" casing was run & cemented in place:

1-Baker guide shoe	1.08'
1-Joint 8-5/8" 32#/ft., J-55, ST&C casing	41.71'
1-Baker float collar	1.92'
27 jts 8-5/8" 32#/ft., J-55 ST&C casing	1115.34'
51 jts 8-5/8" 24#/ft., J-55, ST&C casing	2150.61'
5 jts 8-5/8" 32#/ft., J-55, ST&C Casing	171.73'
84 joints total	3482.40'

K.B. to G.L.	17.60'
Casing set at	3500.00' K.B.
Guide shoe top	3498.91' K.B.
Float Collar top	3455.28' K.B.

Cement or Safety Valve Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Robert N. Enfield TITLE Operator DATE 9/3/85

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

(This space for Federal or State Office use)

ACCEPTED FOR RECORD
PETER W. CHESTER

DATE

SEP 11 1985

See Instructions on Reverse Side
BUREAU OF LAND MANAGEMENT
ROSWELL RESOURCE AREA

SEP 3 1985

RECEIVED

SEP 23 1985

O.C.D.
HOBBS OFFICE