ABANDON*

for 1 hr.

UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

					- '
5. LEA	SE	1		ு க்கி	
NM	15895				
6. IF I	NDIAN, A	LLOTTEE	OR TRIE	BE NAME	
7. UN	IT AGREE	MENT NA	ME	- 3	
8. FAF	RM OR LE	ASE NAM	E :	537.3	
Car	son Fe	deral			
9. WE		1.1.4 4	: 3		
1			÷,		
10. FIE	LD OR W	LDCAT N	AME 4		_
	dcat			3	
		M., OR B	LK. ANI	SURVEY	OF
AR	EA	- 1	ş		
Sec	. 3. T	9S, R3	R1F 🐫		
12. CO	UNTY OR	PARISH	13. ST	ATE	
Cha	ves		NM		
14. API			· ·		_
15. ELI	EVATIONS	S (SHOW	DF, KE	B, AND V	VD.

SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.) 1. oil gas well 12 other well 2. NAME OF OPERATOR Robert N. Enfield 3. ADDRESS OF OPERATOR P.O. Box 2431, Santa Fe, NM 87501 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 1980' FSL & 990' FWL of Sec. 3. AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA SUBSEQUENT REPORT OF: REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL (NOTE: Report results of multiple completion or zone PULL OR ALTER CASING change on Form 9-330.) MULTIPLE COMPLETE CHANGE ZONES

(other) PAGE 2 - SET INTER MEDIATE CASING-X 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Pumped 10 barrels fresh water ahead of cement. Cemented with 1230 sacks Pace Setter Lite "H" with 1#/sack, Hi-Seal and 3% salt, (1.98 cu. ft./sk. yield and 12.4#/gallon weight). Tailed in with 230 sacks Class "C" Neat, (1.32 cu. ft, sk. yield, 14.8#/gallon weight). Displaced with 206.9 barrels fresh water at 500-950 PSI. Bumped plug with 1250 PSI. Plug down at 9:30 PM August 22, 1985. Circulated 45 sacks to surface. Pressure tested casing with 1200 PSI

Subsurface Safety Valve: Manu. and Type		Set @	F	Ft
18. I hereby certify that the foregoing is SIGNED LOUNT N. Enforce		0/3/85		
Robert N. Enfield	(This space for Federal or State office use)	3/3/09		
APPROVED BY	PETER W. CHESTER			

BUREAU OF LAND MANAGEMENT ROSWELL RESOURCE AREA