

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATION	

3a. Indicate Type of Lease
State ☒ Fee ☐
5. State Oil & Gas Lease No.
LG 1348

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO REFRACK OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT TO DRILL FORM C-101 FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. Unit Agreement Name
Name of Operator Yates Petroleum Corporation	8. Farm or Lease Name Charlotte ADK State
Address of Operator 207 South 4th St., Artesia, NM 88210	9. Well No. 1
Location of Well UNIT LETTER <u>E</u> <u>1650</u> FEET FROM THE <u>North</u> LINE AND <u>330</u> FEET FROM THE <u>West</u> LINE SECTION <u>22</u> TOWNSHIP <u>8S</u> RANGE <u>33E</u> N.M.P.M.	10. Field and Pool, or adjacent Chaveroo San Andres
11. Elevation (Show whether DF, RT, GR, etc.) 4368.1' GR	12. County Chaves

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPERATIONS ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☐	
		OTHER <u>Production Casing, Perforate, Treat</u> ☒	

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 4550'. Ran 114 joints 5-1/2" 17# J-55 casing set 4550'. 1-Regular cement nosed guide shoe set 4550'. Super Seal float collar set 4510'. Cemented w/300 sx Class "C" + 3% TF-14 + 3% KCL. Compressive strength of cement - 900 psi in 12 hrs. PD 11:15 AM 12-17-85. Bumped plug to 1000# for 30 minutes, released pressure, float and casing held okay. WOC 18 hrs. WIH and perforated 4447-4501' w/12 .42" holes as follows: 4447, 48, 49, 50, 51, 53, 93, 94 1/2, 96, 98, 99 1/2 and 4501'. Treated perms 4493-4501' (6 holes) w/500 gals 15% NEFE acid. Communicated up to perms at 4447-53'. Swabbed well. No oil or gas. GIH w/cement retainer and squeezed perms 4447-4501' (12 holes) w/100 sx Class C + 2% CaCl2 + .3% CF-14. Squeezed to 3000#. WIH and perforated 4342-4375' w/15 .42" holes as follows: 4342, 45, 57, 60, 62, 64, 66, 68, 69, 70, 71, 72, 73, 74 and 75'. Acidized perms 4342-75' w/1500 gals 15% NEFE acid. Swab tested. WIH and perforated 4270-4310 1/2' w/18 .40" holes as follows: 4270, 72, 74, 76, 78, 79, 80, 81, 82 1/2, 89, 91, 94, 97, 4302, 04, 06, 09 and 10 1/2'. Acidized perms 4270-4310 1/2' w/2000 gals 15% NEFE acid, 18 ball sealers. Swabbing well and testing.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Eddie W. Sady TITLE Production Supervisor DATE 1-9-86

APPROVED BY Eddie W. Sady TITLE Oil & Gas Inspector DATE JAN 10 1986
CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

JAN 10 1986

O.C.D.
HOBBS OFFICE