

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. OIL ☒ GAS ☐ OTHER ☐

2. NAME OF OPERATOR

Haseloff Corporation

3. ADDRESS OF OPERATOR

Box 249, Lovington, NM 88260

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

1980' FSL 1650' FEL

AT SURFACE: Same

AT TOP PROD. INTERVAL: Same

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐

(other) Completion

LEASE

NM-046153-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Miller Federal

9. WELL NO.

9

10. FIELD OR WILDCAT NAME

Tom-Tom San Andres

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 35: T7S, R31E

12. COUNTY OR PARISH

Chaves

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

4360.8' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

1-03-86 Set bridge plug at 4136'. T.D. 4200'.

Schlumberger perforated as follows:

(P-2) 4062, 63, 65, 66, 74, 75, (P-3) 4092, 94, 95, 96,

4103, 04, 05, 10, 11, 4112. - 16 Total shots.

Acidized W/2000 gals. 20% acid, Recovered 118 BBL's fluid - 50% oil cut.

1-04-86 Set bridge plug at 4058'. T.D. 4200'.

Schlumberger perforated as follows:

(P-2) 3993, 94, 98, 4000, 03, 07, 08, 09, 10, 13, 14, 18, 21, 22,

23, 24, 26, 27, 29, 30, 31, 32, 33, 36, 37, 4042. - 27 Total shots.

Acidized W/ 4000 gals. 20% acid, Recovered 280 BBL's fluid - 70% oil cut.

Pulled Bridge Plug.

Subsurface Safety Valve: Manu. and Type

Set @ FL

18. I hereby certify that the foregoing is true and correct

SIGNED

[Signature]

TITLE

Officer MANANA

DATE

1-14-86

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

ELMER A. CHESTER

JAN 23 1986

*See Instructions on Reverse Side

BUREAU OF LAND MANAGEMENT
ROSWELL, NEW MEXICO