

UNITED STATES DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
ROOSEVELT, NEW MEXICO 88240

Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input checked="" type="checkbox"/> Dry Hole	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR John S. Goodrich	8. FARM OR LEASE NAME Phillips Federal
3. ADDRESS OF OPERATOR 4000 N. Big Spring, Suite 109, Midland, Texas 79705	9. WELL NO. 1
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface	10. FIELD AND POOL, OR WILDCAT SE Chaves Queen Gas Area Asso
14. PERMIT NO. 1-10-86	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 18, T14S, R31E
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4047.9' GL	12. COUNTY OR PARISH Chaves
	13. STATE NM

16

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF	<input type="checkbox"/>	PULL OR ALTER CASING	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	MULTIPLE COMPLETE	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	ABANDON*	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	CHANGE PLANS	<input type="checkbox"/>
(Other)			

SUBSEQUENT REPORT OF:

WATER SHUT-OFF	<input type="checkbox"/>	REPAIRING WELL	<input type="checkbox"/>
FRACTURE TREATMENT	<input type="checkbox"/>	ALTERING CASING	<input type="checkbox"/>
SHOOTING OR ACIDIZING	<input type="checkbox"/>	ABANDONMENT*	<input checked="" type="checkbox"/>
(Other)			

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

1. Set open hole packer at 2422' with 25 sx cement on top of it to 2320';
2. Set 75 sx cement plug from 1801' to 1700' - tagged top of cement;
3. Set 45 sx cement plug from 415' to 315';
4. Set 15 sx cement plug from 50' to surface; all plugs placed by Halliburton pumps down drill pipe with 10.1 ppg mud between plugs.
5. Installed dry hole marker April 16, 1986.



I hereby certify that the foregoing is true and correct

SIGNED J. Goodrich TITLE Operator DATE 4-25-86

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

